

Panasonic SMT Capacitors ECH-U and ECH-X - ECH-U(X) Series (Cont.)




Table with columns: Case Size, WV DC, Cap. µF, Dim. H (mm), Digi-Key Part No., Cut Tape Pricing (1, 50, 100), Tape and Reel Qty./Pricing, Panasonic Part No.

Table with columns: Case Size, WV DC, Cap. µF, Dim. H (mm), Digi-Key Part No., Cut Tape Pricing (1, 50, 100), Tape and Reel Qty./Pricing, Panasonic Part No.



For Tape and Reel part number, change CT-ND to TR-ND. RoHS Compliant

Panasonic SMT Capacitors ECP-U (SF Submicron)



FEATURES: • Small in size • Low ESR • Excellent sound quality
APPLICATIONS: • Coupling • Decoupling • Noise Reduction
SPECIFICATIONS: • Operating Temperature: -40°C ~ 85°C • Dissipation Factor: 1.5% maximum (20°C, 1kHz)
• Withstand Voltage: Between terminals rated voltage (VDC) x 175%, 1 to 5s • Insulation Resistance: Cs0.33µF: 1000MΩ minimum (20°C, 16VDC, 60s), C>0.33µF: 300MΩ minimum (20°C, 16VDC, 60s) • Soldering Reflow Conditions: 240°C maximum and 30 seconds maximum at more than 210°C (temperature at cap surface)
Note: Solder paste/flux shall have less than 0.1wt% halogen content.
Storage: The unpacked products shall be kept in polyethylene bag together with well-dried silica-gel (from 5g to 10g) or be kept in storage at a temperature of 25°C, with a humidity less than 50% RH. This capacitor shall be used in only reflow method. Don't use in flow, dipping, or VPS soldering method.
A recommended solder paste thickness is between 0.10 (mm) and 0.15 (mm).




Table with columns: Type / Case Size, Dimensions of Land - mm (A, B, C)

Table with columns: Case Size, WV DC, Cap. µF, Dimensions - mm (L, W, H, e1, g), Type, Digi-Key Part No., Cut Tape Pricing (1, 50, 100), Digi-Key Part No., Tape and Reel Qty./Pricing, Panasonic Part No.

Digi-Reel Most SMT cutdown parts are available on a Digi-Reel. For Digi-Reel part number, change 1-ND to 6-ND or CT-ND to DKR-ND. See Digi-Key Services on page 2 for additional information.

Free shipping on orders over \$200 CAD! All prices in Canadian dollars and include duty and brokerage fees.

1-800-344-4539 • www.digikey.ca • 218-681-6674 • Fax: 218-681-3380

(CA2011) 1865