




AC 轴向风扇



NMB-MAT AC 轴向风扇适用于多种应用。它们采用“漏斗”型样式将空气压出，是为如电源盒等被许多部件围绕且仅有极少通风面积的特定位置降温的理想选择。

尺寸 (mm)	轴承	电压	输入功率 (W)	气流 (CFM)	噪音 (dB)	引线	Digi-Key 零件编号	单价			NMB Technologies 零件编号	护指罩	单价		
								1	5	10					
60x30	滚珠	115	4.0	9.18	29	22AWG, 300mm 引线	P12871-ND	16.88	14.52	12.49	2412PS-12W-B30-A00	CR221-ND	.68		
80x25	滚珠	115	5.0	19.77	33	22AWG, 300mm 引线	P12872-ND	17.00	14.62	12.58	3110PS-12W-B30-A00	CR229-ND	.70		
80x38	滚珠	115	4.0	18.0	31	0.110 端子	P12988-ND	16.50	14.19	12.21	3115FS-12T-B00-A00	CR229-ND	.70		
		115	4.0	19.4	25	22AWG, 300mm 引线	P12993-ND	17.00	14.62	12.58	3115PS-12W-B10-A00	CR229-ND	.70		
		230	6.5	20.0	35	0.110 端子	P12875-ND	16.50	14.19	12.21	3115FS-23T-B10-A00	CR229-ND	.70		
		230	6.5	20.0	35	22AWG, 300mm 引线	P12879-ND	16.50	14.19	12.21	3115FS-23W-B10-A00	CR229-ND	.70		
		115	6.0	22.0	36	0.110 端子	P12873-ND	17.00	14.62	12.58	3115FS-12T-B10-A00	CR229-ND	.70		
		115	6.0	22.0	36	22AWG, 300mm 引线	P12877-ND	16.50	14.19	12.21	3115FS-12W-B10-A00	CR229-ND	.70		
		230	5.0	22.0	26	22AWG, 300mm 引线	P12997-ND	17.00	14.62	12.58	3115PS-23W-B10-A00	CR229-ND	.70		
		230	6.0	26.0	34	0.110 端子	P12995-ND	17.00	14.62	12.58	3115PS-23T-B20-A00	CR229-ND	.70		
		230	6.0	26.0	34	22AWG, 300mm 引线	P12998-ND	17.00	14.62	12.58	3115PS-23W-B20-A00	CR229-ND	.70		
		115	7.0	27.0	40	0.110 端子	P12989-ND	16.50	14.19	12.21	3115FS-12T-B20-A00	CR229-ND	.70		
		115	7.0	27.0	40	22AWG, 300mm 引线	P12990-ND	16.50	14.19	12.21	3115FS-12W-B20-A00	CR229-ND	.70		
		230	7.5	28.0	40	22AWG, 300mm 引线	P12992-ND	16.50	14.19	12.21	3115PS-23W-B20-A00	CR229-ND	.70		
		115	7.0	31.77	38	0.110 端子	P12891-ND	17.00	14.62	12.58	3115PS-12T-B30-A00	CR229-ND	.70		
		115	8.5	32.0	44	0.110 端子	P12874-ND	17.00	14.62	12.58	3115FS-12T-B30-A00	CR229-ND	.70		
		115	8.5	32.0	44	22AWG, 300mm 引线	P12878-ND	17.00	14.62	12.58	3115FS-12W-B30-A00	CR229-ND	.70		
		115	7.0	32.0	38	22AWG, 300mm 引线	P12882-ND	17.00	14.62	12.58	3115PS-12W-B30-A00	CR229-ND	.70		
		230	8.0	32.0	38	0.110 端子	P12996-ND	17.00	14.62	12.58	3115PS-23T-B30-A00	CR229-ND	.70		
		230	8.0	32.0	38	22AWG, 300mm 引线	P12999-ND	17.00	14.62	12.58	3115PS-23W-B30-A00	CR229-ND	.70		
		230	8.0	33.0	44	0.110 端子	P12876-ND	17.00	14.62	12.58	3115FS-23T-B30-A00	CR229-ND	.70		
		230	8.0	33.0	44	22AWG, 300mm 引线	P12880-ND	17.00	14.62	12.58	3115FS-23W-B30-A00	CR229-ND	.70		
		92x25	滚珠	115	6.0	20.0	25	0.110 端子	P13100-ND	17.25	14.84	12.77	3610PS-12T-B10-A00	CR220-ND	.77
				115	6.0	20.0	25	22AWG, 300mm 引线	P13102-ND	17.25	14.84	12.77	3610PS-12W-B10-A00	CR220-ND	.77
				230	6.0	20.0	26	0.110 端子	P13103-ND	17.25	14.84	12.77	3610PS-23T-B10-A00	CR220-ND	.77
				115	6.0	28.0	35	0.110 端子	P13101-ND	17.25	14.84	12.77	3610PS-12T-B20-A00	CR220-ND	.77
230	6.0			28.0	35	0.110 端子	P13104-ND	17.25	14.84	12.77	3610PS-23T-B20-A00	CR220-ND	.77		
115	9.0			34.5	38	22AWG, 300mm 引线	P12884-ND	17.25	14.84	12.77	3610PS-12W-B30-A00	CR220-ND	.77		
230	10.0			34.5	39	22AWG, 300mm 引线	P12886-ND	17.25	14.84	12.77	3610PS-23W-B30-A00	CR220-ND	.77		
115	9.0			34.6	38	0.110 端子	P12883-ND	17.25	14.84	12.77	3610PS-12T-B30-A00	CR220-ND	.77		
230	10.0			34.6	39	0.110 端子	P12885-ND	17.25	14.84	12.77	3610PS-23T-B30-A00	CR220-ND	.77		
119x25	滚珠			115	7.0	53.0	30	0.110 端子	P12887-ND	17.25	14.84	12.77	4710PS-12T-B20-A00	CR224-ND	.91
230	8.0	53.0	30	0.110 端子	P12889-ND	17.25	14.84	12.77	4710PS-23T-B20-A00	CR224-ND	.91				
115	11.0	70.6	38	0.110 端子	P12888-ND	17.25	14.84	12.77	4710PS-12T-B30-A00	CR224-ND	.91				
230	11.0	70.6	38	0.110 端子	P12890-ND	17.25	14.84	12.77	4710PS-23T-B30-A00	CR224-ND	.91				
119x38	滚珠	115	5.5	49.4	28	0.110 端子	P12891-ND	16.25	13.98	12.03	4715MS-12T-B10-A00	CR224-ND	.91		
		230	7.5	67.0	30	0.110 端子	P13110-ND	16.25	13.98	12.03	4715MS-23T-B20-A00	CR224-ND	.91		
		115	7.0	67.1	30	0.110 端子	P12892-ND	16.25	13.98	12.03	4715MS-12T-B20-A00	CR224-ND	.91		
		115	10.0	70.0	33	0.110 端子	P12895-ND	16.88	14.52	12.49	4715FS-12T-B10-D00	CR224-ND	.91		
		230	9.0	70.0	70	0.110 端子	P12897-ND	16.88	14.52	12.49	4715FS-23T-B10-D00	CR224-ND	.91		
		115	9.8	80.0	36	0.110 端子	P13105-ND	16.88	14.52	12.49	4715FS-12T-B20-D00	CR224-ND	.91		
		230	11.0	88.2	37	0.110 端子	P13111-ND	16.25	13.98	12.03	4715MS-23T-B30-A00	CR224-ND	.91		
		115	14.5	102.2	41	0.110 端子	P12893-ND	16.25	13.98	12.03	4715MS-12T-B50-A00	CR224-ND	.91		
		115	14.5	90.0	39	0.110 端子	P13106-ND	16.88	14.52	12.49	4715FS-12T-B30-D00	CR224-ND	.91		
		115	13.0	95.0	39	0.110 端子	P13109-ND	16.25	13.98	12.03	4715MS-12T-B40-A00	CR224-ND	.91		
		230	13.0	95.0	39	0.110 端子	P13112-ND	16.25	13.98	12.03	4715MS-23T-B40-A00	CR224-ND	.91		
		115	14.0	100.0	42	0.110 端子	P13107-ND	16.25	13.98	12.03	4715FS-12T-B40-D00	CR224-ND	.91		
		230	14.0	100.0	100	0.110 端子	P13108-ND	16.88	14.52	12.49	4715FS-23T-B40-D00	CR224-ND	.91		
		230	14.0	102.4	41	0.110 端子	P12894-ND	16.25	13.98	12.03	4715MS-23T-B50-A00	CR224-ND	.91		
		115	14.4	110	45	0.110 端子	P12896-ND	16.25	13.98	12.03	4715FS-12T-B50-D00	CR224-ND	.91		
		230	14.0	110	110	0.110 端子	P12898-ND	16.25	13.98	12.03	4715FS-23T-B50-D00	CR224-ND	.91		
		150x172x38	滚珠	115	32.0	21.2	56	0.110 端子	P12899-ND	51.85	44.60	38.37	5915PC-12T-B30-A00	CR191-ND	2.48
				230	35.0	21.2	56	0.110 端子	P12900-ND	51.85	44.60	38.37	5915PC-23T-B30-A00	CR191-ND	2.48
230	18.0			102.3	38	0.110 端子	P13113-ND	51.85	44.60	38.37	5915PC-23T-B10-A00	CR191-ND	2.48		

DC 风扇 FBL 系列



特点:

- 百叶窗式设计，可在额定标准条件下增加气流并降低湍流噪音
- 水波轴承技术

技术规格:

- 工作温度: -10°C ~ 70°C (65%RH)
- 塑料等级: 全部 Panaflo 风扇均使用 UL 94V-0 塑料 (易燃性级别) 制造

• 噪音数据: 从距离半电波暗室中悬浮风扇进气侧 1 米处测得的噪音数据 (最大背景噪音 13dB-A)

• 预期寿命: 50,000 小时 (40°C, 65%RH)

工作电压 (VDC)	尺寸 (mm)	输入功率 (W)	最大气流 (CFM)	最大气流压力 (mmH ₂ O)	最大噪音 (dB-A)	引线长度 (mm)	Digi-Key 零件编号	单价			NMB Technologies 零件编号	护指罩	单价			
标称	范围	平方 x 厚度						1	5	10	50	100				
12	7-13.5	60 x 25.5	3.24	15.89	4.7	42.0	315	P10893-ND	8.75	7.53	6.48	5.81	5.25	FBL06A12U1A	CR221-ND	.68
12	7-13.8	60 x 25.5	2.64	14.83	4.1	36.0	315	P10892-ND	8.50	7.31	6.29	5.65	5.10	FBL06A12H1A	CR221-ND	.68
12	7-13.8	60 x 25.5	2.04	13.06	3.0	32.0	315	P10891-ND	8.50	7.31	6.29	5.65	5.10	FBL06A12M1A	CR221-ND	.68
12	7-13.8	60 x 25.5	1.68	14.83	2.1	29.0	315	P10890-ND	8.75	7.53	6.48	5.81	5.25	FBL06A12L1A	CR221-ND	.68
24	14-27.6	60 x 25.5	3.24	15.89	4.7	42.0	315	P11017-ND	8.75	7.53	6.48	5.81	5.25	FBL06A24U1A	CR221-ND	.68
24	14-27.6	60 x 25.5	1.68	14.83	2.1	29.0	315	P11014-ND	8.50	7.31	6.29	5.65	5.10	FBL06A24L1A	CR221-ND	.68
12	7-13.5	80 x 25.5	4.32	35.31	4.7	42.0	300	P11082-ND	9.25	7.96	6.85	6.15	5.55	FBL08A12U1BX	CR180-ND	.93
12	7-13.8	80 x 25.5	4.32	35.31	4.0	42.0	300	P10897-ND	8.75	7.53	6.48	5.81	5.25	FBL08A12U1A	CR180-ND	.93
12	7-13.8	80 x 25.5	3.00	30.01	2.9	39.0	300	P10896-ND	8.50	7.31	6.29	5.65	5.10	FBL08A12H1A	CR180-ND	.93
12	7-13.8	80 x 25.5	2.04	24.71	2.0	33.0	300	P10895-ND	8.75	7.53	6.48	5.81	5.25	FBL08A12M1A	CR180-ND	.93
12	7-13.8	80 x 25.5	1.20	17.30	1.1	26.0	300	P10894-ND	—	—	—	—	—	FBL08A12L1A	CR180-ND	.93
24	14-27.6	80 x 25.5	3.00	30.00	2.9	39.0	300	P11020-ND	8.50	7.31	6.29	5.65	5.10	FBL08A24H1A	CR180-ND	.93
24	14-27.6	80 x 25.5	2.04	24.71	2.0	33.0	300	P11019-ND	8.50	7.31	6.29	5.65	5.10	FBL08A24M1A	CR180-ND	.93
24	14-27.6	80 x 25.5	1.20	17.30	1.1	26.0	300	P11018-ND	—	—	—	—	—	FBL08A24L1A	CR180-ND	.93
12	7-13.5	92 x 25.5	3.48	45.89	3.3	40.0	295	P10900-ND	8.50	7.31	6.29	5.65	5.10	FBL09A12H1A	CR220-ND	.77
12	7-13.5	92 x 25.5	3.48	45.9	3.3	40.0	295	P11083-ND	9.25	7.96	6.85	6.15	5.55	FBL09A12H1BX	CR220-ND	.77
12	7-13.8	92 x 25.5	2.40	35.99	2.3	36.0	295	P10899-ND	8.50	7.31	6.29	5.65	5.10	FBL09A12M1A	CR220-ND	