




防护接头

直引线


No. of Pins	Dim. A In. (mm)
10	1.26 (32.00)
14	1.46 (37.08)
16	1.56 (39.62)
20	1.76 (44.70)
26	2.06 (52.32)
34	2.46 (62.48)
40	2.76 (70.10)
50	3.26 (82.80)
60	3.76 (95.50)



弹出锁钩，每个连接器需要两个，单独出售

直角


No. of Pins	Dim. A In. (mm)
10	1.26 (32.00)
14	1.46 (37.08)
16	1.56 (39.62)
20	1.76 (44.70)
26	2.06 (52.32)
34	2.46 (62.48)
40	2.76 (70.10)
50	3.26 (82.80)
60	3.76 (95.50)



弹出锁钩，每个连接器需要两个，单独出售


直引线绕接

弹出锁钩，每个连接器需要两个，单独出售



直角绕接

弹出锁钩，每个连接器需要两个，单独出售



技术规格:

- 触点: 磷青铜, 标准
- 触点涂层: 在 50μ 英寸镀银层上再镀 10μ 英寸金 (配接区域)
- 绝缘体材料: UL 94V-0 阻燃热塑性塑料
- 颜色: 蓝色
- 工作温度: -55°C - 125°C
- 额定电流: 每个接触最大 1A
- 电介质耐受电压: 在海平面大于 500 VDC
- 绝缘电阻: 大于 5x10⁹Ω
- 美国国防部 Mil-C-83503/20、21 标准

触点数	描述	Digi-Key 零件编号	单价			
			1	10	100	1,000
防护接头 - 镀金						
10	直引线	CHS10G-ND	1.12	.85	.65	.47
	直角	CHR10G-ND	1.12	.85	.65	.47
	直引线 WW	CHW10G-ND	2.29	1.74	1.34	.97
	直角 WW	CHA10G-ND	2.29	1.74	1.34	.97
14	直引线	CHS14G-ND	1.43	1.09	.83	.60
	直角	CHR14G-ND	1.43	1.09	.83	.60
	直引线 WW	CHW14G-ND	2.91	2.21	1.70	1.23
	直角 WW	CHA14G-ND	2.91	2.21	1.70	1.23

触点数	描述	Digi-Key 零件编号	单价			
			1	10	100	1,000
16	直引线	CHS16G-ND	1.58	1.20	.92	.67
	直角	CHR16G-ND	1.58	1.20	.92	.67
	直引线 WW	CHW16G-ND	3.29	2.50	1.91	1.38
20	直引线	CHS20G-ND	1.67	1.27	.98	.71
	直角	CHR20G-ND	1.67	1.27	.98	.71
	直引线 WW	CHW20G-ND	3.41	2.59	1.98	1.43
26	直引线	CHS26G-ND	2.05	1.56	1.19	.86
	直角	CHR26G-ND	2.05	1.56	1.19	.86
	直引线 WW	CHW26G-ND	4.09	3.11	2.38	1.72
34	直引线	CHS34G-ND	2.45	1.86	1.43	1.03
	直角	CHR34G-ND	2.45	1.86	1.43	1.03
	直引线 WW	CHW34G-ND	4.90	3.72	2.85	2.06
40	直引线	CHS40G-ND	2.98	2.26	1.73	1.25
	直角	CHR40G-ND	2.98	2.26	1.73	1.25
	直引线 WW	CHW40G-ND	5.98	4.54	3.48	2.51
50	直引线	CHS50G-ND	3.35	2.54	1.95	1.41
	直角	CHR50G-ND	3.35	2.54	1.95	1.41
	直引线 WW	CHW50G-ND	6.70	5.08	3.89	2.81
60	直引线 ST* (带罩壳)	CHB60G-ND	5.44	4.13	3.16	2.29
	直引线 WW* (带罩壳)	CHC60G-ND	5.44	4.13	3.16	2.29
	直角 ST* (带罩壳)	CHD60G-ND	3.98	3.02	2.32	1.67
	直角 WW* (带罩壳)	CHE60G-ND	5.44	4.13	3.16	2.29
CLKS01-ND 弹出锁钩 - 短 (每个连接器需要 2 个)37/2			
CLKS02-ND 弹出锁钩: 长 - 带应力消除: (每个连接器需要 2 个)37/2			

* 内含弹出锁钩




防护接头

技术规格:

- 材料和表面处理: 外壳和锁销 - 黑色热塑性塑料, 定级 94V-0.
- 触点表面处理: 接线柱/引脚配接端镀 15μ 或 30μ 金, 接线端镀 100μ 锡, 整个触点底层镀 0.00050 镍
- 连接器经过 Under-writers Laboratories Inc. 的元件程序认证, 文件号 E28476
- 连接器经 Canadian Standards Association 认证, 文件编号 LR16455.
- 0.025" (0.64mm) 方形 接线柱, 0.240" (6.10mm) 配接柱长度

直引线

No. of Pins	Dim. A In. (mm)
10	1.26 (32.00)
14	1.46 (37.08)
16	1.56 (39.62)
20	1.76 (44.70)
24	1.96 (49.78)
26	2.06 (52.32)
30	2.26 (57.40)
34	2.46 (62.48)
40	2.76 (70.10)
50	3.26 (82.80)
60	3.76 (95.50)
64	3.96 (100.58)



弹出锁钩，每个连接器需要两个，单独出售

触点数	触点镀金	柱长度 英寸 (mm)	Digi-Key 零件编号	单价		AMP 零件编号
				1	10	
不带锁销的引脚接头						
20	30μ"	.155 (3.94)	AHJ20K-ND	2.63	2.37	102156-4
30	15μ"	.110 (2.79)	AHS30G-ND	4.53	4.08	102153-7
不带锁销的引脚接头, 符合 RoHS 规范要求						
10	15μ"	.110 (2.79)	AHS10H-ND	1.05	.95	5102153-1
	30μ"	.110 (2.79)	AHS10L-ND	1.20	1.08	5102154-1
14	15μ"	.155 (3.94)	AHJ10H-ND	1.20	1.08	5102155-1
	30μ"	.110 (2.79)	AHS14H-ND	1.45	1.31	5102153-2
16	30μ"	.110 (2.79)	AHS14L-ND	1.55	1.40	5102154-2
	15μ"	.110 (2.79)	AHS16H-ND	1.65	1.49	5102153-3
20	30μ"	.110 (2.79)	AHS16L-ND	1.90	1.71	5102154-3
	15μ"	.155 (3.94)	AHJ16H-ND	1.90	1.71	5102155-3
24	30μ"	.155 (3.94)	AHJ16L-ND	2.81	2.34	5102156-3
	15μ"	.110 (2.79)	AHS20H-ND	2.05	1.85	5102153-4
30	30μ"	.110 (2.79)	AHS20L-ND	2.25	2.03	5102154-4
	15μ"	.155 (3.94)	AHJ20L-ND	3.42	3.08	5102156-4
26	15μ"	.110 (2.79)	AHS24H-ND	2.40	2.16	5102153-5
	30μ"	.110 (2.79)	AHS24L-ND	2.65	2.39	5102154-5
30	30μ"	.155 (3.94)	AHJ24L-ND	2.90	2.61	5102156-5
	15μ"	.110 (2.79)	AHS26H-ND	2.60	2.34	5102153-6
34	30μ"	.110 (2.79)	AHS26L-ND	2.75	2.48	5102154-6
	15μ"	.155 (3.94)	AHJ26H-ND	3.16	2.85	5102155-6
40	30μ"	.155 (3.94)	AHJ26L-ND	2.99	2.70	5102156-6
	15μ"	.110 (2.79)	AHS30H-ND	4.10	3.70	5102153-7
50	30μ"	.110 (2.79)	AHS30L-ND	4.79	4.32	5102154-7
	15μ"	.110 (2.79)	AHS34H-ND	4.12	3.71	5102153-8
60	30μ"	.110 (2.79)	AHS34L-ND	3.39	3.06	5102154-8
	15μ"	.155 (3.94)	AHJ34H-ND	3.39	3.06	5102155-8
64	30μ"	.155 (3.94)	AHJ34L-ND	3.59	3.24	5102156-8
	15μ"	.110 (2.79)	AHS40H-ND	3.79	3.42	5102153-9
50	30μ"	.110 (2.79)	AHS40L-ND	3.89	3.51	5102154-9
	15μ"	.155 (3.94)	AHJ40H-ND	4.48	4.03	5102155-9
60	30μ"	.155 (3.94)	AHJ40L-ND	4.14	3.73	5102156-9
	15μ"	.110 (2.79)	AHS50H-ND	4.49	4.05	1-5102153-0
60	30μ"	.110 (2.79)	AHS50L-ND	4.59	4.14	1-5102154-0
	15μ"	.155 (3.94)	AHJ50H-ND	5.28	4.76	1-5102155-0
60	30μ"	.155 (3.94)	AHJ50L-ND	5.01	4.51	1-5102156-0
	15μ"	.110 (2.79)	AHS60L-ND	5.34	4.81	1-5102154-1
64	30μ"	.155 (3.94)	AHJ60L-ND	6.42	5.78	1-5102156-1
	15μ"	.110 (2.79)	AHS64H-ND	5.91	5.32	1-5102153-2
64	30μ"	.110 (2.79)	AHS64L-ND	5.46	4.92	1-5102154-2
	15μ"	.155 (3.94)	AHJ64H-ND	8.43	7.59	1-5102155-2
64	30μ"	.155 (3.94)	AHJ64L-ND	5.70	5.13	1-5102156-2
	带动作引脚触点的引脚接头					
34	30μ"	.174 (4.42)	AHA34A-ND	5.67	5.11	499582-8
带动作引脚触点的引脚接头, 符合 RoHS 规范要求						
10	30μ"	.174 (4.42)	AHA10B-ND	1.90	1.71	1658694-6
14	30μ"	.174 (4.42)	AHA14B-ND	2.60	2.34	1658694-7
16	30μ"	.174 (4.42)	AHA16B-ND	2.90	2.61	1658694-8
20	30μ"	.174 (4.42)	AHA20B-ND	3.39	3.06	1658694-1
24	30μ"	.174 (4.42)	AHA24B-ND	4.09	3.69	1658694-9
26	30μ"	.174 (4.42)	AHA26B-ND	4.29	3.87	1658694-2
30	30μ"	.174 (4.42)	AHA30B-ND	4.84	4.36	1-1658694-0
34	30μ"	.174 (4.42)	AHA34B-ND	5.28	4.76	1-1658694-1
40	30μ"	.174 (4.42)	AHA40B-ND	5.82	5.24	1-1658694-3
64	30μ"	.174 (4.42)	AHA64B-ND	8.85	7.97	1658694-5

(转下页)