




TPM Series Multianode Ultra Low ESR Surface Mount Tantalum Capacitors

Low ESR, high capacitance and high ripple current are the key parameters for processor filtering. Multianode configuration within a standard E case package meets these requirements • Temperature Range: -55°C - 125°C



Table with dimensions in mm: L ±0.20, W +0.20, -0.10, H +0.20, -0.10, W1 ±0.20, A +0.30, -0.20, S (Min.). Includes case size codes D, E, Y, V.



Main product table with columns: Rated Voltage (V), Capacitance (µF), Capacitance Tolerance %, Case Size, DF % Maximum, DCL (µA) Maximum, ESR Maximum (mΩ)@100kHz, Digi-Key Part No., Cut Tape Price Each (1, 10, 100), Digi-Key Part No., Tape and Reel Qty/Pricing, and AVX Part No.

F

† 478-3448-ND TPM Series Capacitors Kit 5 each of values denoted (85 total pieces). See Digi-Key's website for complete list of parts. 38.21

Digi-Reel Most SMT cutdown parts are available on a Digi-Reel. For Digi-Reel part number, change 1-ND to 6-ND or CT-ND to DKR-ND. See Digi-Key Services on page 2 for additional information.

Free shipping on orders over €65! All prices in euro and include duties. (EU2011-EN) 1763