



# Leaded Varistors (Cont.)

Maximum Allowable Voltage (V)		Varistor Voltage @ 1mA ±10% (V)	Maximum Clamping Voltage		iMax 8/20 μs A	Dimensions (mm)			Digi-Key Part No.	Pricing			Epcos Part No.					
AC	DC		V	A		LS ±1	A ±1	Ø Max.		T Max.	H Max.	1		10	1,000	5,000		
300	385	470	775	5.0	800	5.0	2.1	7.0	4.7	8.5	.6	495-1422-ND	.08	.72	6.00	34.20	31.92/M	S05K300E2
150	200	240	395	10	1750	5.0	1.8	9.0	4.1	11.0	.6	495-1424-ND	.12	1.01	8.40	47.88	44.69/M	S07K150E2
250	320	390	650	10	1750	5.0	1.9	9.0	4.5	11.0	.6	495-1425-ND	.12	1.01	8.40	47.88	44.69/M	S07K250E2
275	350	430	710	10	1750	5.0	2.0	9.0	4.6	11.0	.6	495-1426-ND	.12	1.01	8.40	47.88	44.69/M	S07K275E2
300	385	470	775	10	1750	5.0	2.1	9.0	4.7	11.0	.6	495-1427-ND	.12	1.01	8.40	47.88	44.69/M	S07K300E2
320	420	510	845	10	1750	5.0	2.3	9.0	4.6	11.0	.6	495-1428-ND	.12	1.01	8.40	47.88	44.69/M	S07K320E2
140	180	220	360	25	3500	7.5	1.9	12.0	4.6	14.5	.8	495-1429-ND	.22	1.87	15.60	88.92	83.00/M	S10K140E2
150	200	240	395	25	3500	7.5	2.0	12.0	4.7	14.5	.8	495-1430-ND	.22	1.87	15.60	88.92	83.00/M	S10K150E2
175	225	270	455	25	3500	7.5	2.2	12.0	4.9	14.5	.8	495-1431-ND	.22	1.87	15.60	88.92	83.00/M	S10K175E2
250	320	390	650	25	3500	7.5	2.1	12.0	5.2	14.5	.8	495-1432-ND	.22	1.87	15.60	88.92	83.00/M	S10K250E2
275	350	430	710	25	3500	7.5	2.2	12.0	5.4	14.5	.8	495-1433-ND	.22	1.87	15.60	88.92	83.00/M	S10K275E2
300	385	470	775	25	3500	7.5	2.3	12.0	5.6	14.5	.8	495-1434-ND	.22	1.87	15.60	88.92	83.00/M	S10K300E2
420	560	680	1120	25	3500	7.5	3.5	12.0	7.4	15.0	.8	495-1435-ND	.25	2.16	18.00	102.60	95.76/M	S10K420E2
130	170	205	340	50	6000	7.5	1.9	15.5	4.6	18.5	.8	495-1436-ND	.35	3.02	25.20	143.64	134.07/M	S14K130E2
140	180	220	360	50	6000	7.5	2.0	15.5	4.7	18.5	.8	495-1437-ND	.35	3.02	25.20	143.64	134.07/M	S14K140E2
150	200	240	395	50	6000	7.5	2.1	15.5	4.8	18.5	.8	495-1438-ND	.35	3.02	25.20	143.64	134.07/M	S14K150E2
175	225	270	455	50	6000	7.5	2.2	15.5	4.9	18.5	.8	495-1439-ND	.35	3.02	25.20	143.64	134.07/M	S14K175E2
250	320	390	650	50	6000	7.5	2.1	15.5	5.2	18.5	.8	495-1440-ND	.35	3.02	25.20	143.64	134.07/M	S14K250E2
275	350	430	710	50	6000	7.5	2.2	15.5	5.4	18.5	.8	495-1441-ND	.35	3.02	25.20	143.64	134.07/M	S14K275E2
300	385	470	775	50	6000	7.5	2.3	15.5	5.6	18.5	.8	495-1442-ND	.35	3.02	25.20	143.64	134.07/M	S14K300E2
130	170	205	340	100	10000	10.0	2.0	21.5	5.0	25.5	1.0	495-1443-ND	.47	4.02	33.50	199.95	178.22/M	S20K130E2
140	180	220	360	100	10000	10.0	2.1	21.5	5.1	25.5	1.0	495-1444-ND	.47	4.02	33.50	199.95	178.22/M	S20K140E2
150	200	240	395	100	10000	10.0	2.2	21.5	5.2	25.5	1.0	495-1445-ND	.46	3.96	33.00	188.10	175.56/M	S20K150E2
175	225	270	455	100	10000	10.0	2.3	21.5	5.3	25.5	1.0	495-1446-ND	.48	4.11	34.25	195.23	182.21/M	S20K175E2
250	320	390	650	100	10000	10.0	2.4	21.5	5.7	25.5	1.0	495-1447-ND	.51	4.35	36.25	206.63	192.85/M	S20K250E2
275	350	430	710	100	10000	10.0	2.6	21.5	5.8	25.5	1.0	495-1448-ND	.53	4.50	37.50	213.75	199.50/M	S20K275E2
300	385	470	775	100	10000	10.0	2.8	21.5	6.1	25.5	1.0	495-1449-ND	.54	4.62	38.50	219.45	204.82/M	S20K300E2
<b>Automotive Series - Fig. 2</b>																		
14	16	22	43	10	1000	7.5	1.5	17.0	5.0	20.5	.8	495-1450-ND	.34	2.92	24.30	138.51	129.28/M	S14K14A4UTO
14	16	22	43	20	2000	10.0	1.6	23.0	5.4	27.5	1.0	495-1451-ND	.56	4.80	40.00	228.00	212.80/M	S20K14A4UTO

RoHS Compliant


# TDK Multilayer Chip Varistors for Surge and Static Protection AVR and AVRL Series



Features: • No polarity due to symmetrical current-voltage characteristics • Excellent electrostatic absorption capability • Can replace a Zener diode and capacitor combination

Specifications: • Operating Temperature: -40°C - 125°C

Size Code	Dimensions - mm						
	L	W	T	B (Min.)	a	b	c
0402	1.0	0.5	0.5	0.1	0.3 - 0.5	0.35 - 0.45	0.4 - 0.6
0603	1.6	0.8	0.8	0.2	0.6 - 0.8	0.6 - 0.8	0.6 - 0.8
0805	2.0	1.25	1.0	0.2	0.9 - 1.2	0.7 - 0.9	0.9 - 1.2



## AVR Series

Size Code	Varistor Voltage (VDC @ 1mA)	Maximum Continuous Voltage (VDC)	Clamping Voltage (8/20μs)	Maximum Peak Current (A)	Capacitance (pF)	Digi-Key Part No.	Cut Tape Pricing			Digi-Key Part No.	Tape and Reel		TDK Part No.
							1	10	100		Qty.	Pricing	
0402	8	5.5	14 (1A)	25	650	445-2532-1-ND	.12	1.11	8.50	445-2532-2-ND	10,000	44.00/M	AVR-M1005C080MTAAB
			15 (1A)	3	100	445-2533-1-ND	.12	1.11	8.50	445-2533-2-ND	10,000	44.00/M	AVR-M1005C080MTABB
	19 (1A)	1	33	445-2539-1-ND	.12	1.11	8.50	445-2539-2-ND	10,000	44.00/M	AVR-M1005C080MTACB		
	20 (1A)	10	130	445-2534-1-ND	.12	1.11	8.50	445-2534-2-ND	10,000	44.00/M	AVR-M1005C120MTAAB		
0603	12	7.5	20 (1A)	4	40	445-2535-1-ND	.12	1.11	8.50	445-2535-2-ND	10,000	44.00/M	AVR-M1005C270MTAAB
			50 (1A)	1	15	445-2536-1-ND	.12	1.11	8.50	445-2536-2-ND	10,000	44.00/M	AVR-M1005C270MTABB
	15 (2A)	30	650	445-2537-1-ND	.18	1.66	12.75	445-2537-2-ND	4,000	71.00/M	AVR-M1608C080MTAAB		
	20 (2A)	50	1050	445-2538-1-ND	.18	1.66	12.75	445-2538-2-ND	4,000	71.00/M	AVR-M1608C120MT6AB		
	15	400	445-2539-1-ND	.18	1.66	12.75	445-2539-2-ND	4,000	71.00/M	AVR-M1608C120MT2AB			
	30 (2A)	30	600	445-2540-1-ND	.18	1.66	12.75	445-2540-2-ND	4,000	71.00/M	AVR-M1608C180MT6AB		
	22	16	34 (2A)	30	560	445-2541-1-ND	.18	1.66	12.75	445-2541-2-ND	4,000	71.00/M	AVR-M1608C220KT6AB
				10	210	445-2542-1-ND	.18	1.66	12.75	445-2542-2-ND	4,000	71.00/M	AVR-M1608C220KT2AB
	27	19	42 (2A)	48	430	445-2543-1-ND	.18	1.66	12.75	445-2543-2-ND	4,000	71.00/M	AVR-M1608C270KT6AB
				20	160	445-2544-1-ND	.18	1.66	12.75	445-2544-2-ND	4,000	71.00/M	AVR-M1608C270KT2AB
17		52 (2A)	2	30	445-2545-1-ND	.18	1.66	12.75	445-2545-2-ND	4,000	71.00/M	AVR-M1608C270MTAAB	
			15	15	445-2546-1-ND	.18	1.66	12.75	445-2546-2-ND	4,000	71.00/M	AVR-M1608C270MTABB	
0805	12	7.5	20 (5A)	60	1000	445-2547-1-ND	.33	3.04	23.38	445-2547-2-ND	2,000	131.00/M	AVR-M2012C120MT6AB
			38 (5A)	100	800	445-2548-1-ND	.33	3.04	23.38	445-2548-2-ND	2,000	131.00/M	AVR-M2012C220KT6AB
	39	28	62 (5A)	100	430	445-2549-1-ND	.33	3.04	23.38	445-2549-2-ND	2,000	131.00/M	AVR-M2012C390KT6AB


## AVRL Series

Size Code	Typical Varistor Voltage (VDC @ 1mA)	Maximum Continuous Voltage (VDC)	Capacitance (pF)	Digi-Key Part No.	Cut Tape Pricing			Digi-Key Part No.	Tape and Reel		TDK Part No.
					1	10	100		Qty.	Pricing	
0402	90	10	1.1	445-2560-1-ND	.18	1.66	12.75	445-2560-2-ND	10,000	66.00/M	AVRL101A1R1NTA
	39	10	1.1	445-2561-1-ND	.18	1.66	12.75	445-2561-2-ND	10,000	66.00/M	AVRL101A1R1NTB
	27	10	3.3	445-2562-1-ND	.18	1.66	12.75	445-2562-2-ND	10,000	66.00/M	AVRL101A3R3FTA
0603	90	10	1.1	445-2563-1-ND	.24	2.21	17.01	445-2563-2-ND	4,000	95.00/M	AVRL161A1R1NTA
	39	10	1.1	445-2564-1-ND	.24	2.21	17.01	445-2564-2-ND	4,000	95.00/M	AVRL161A1R1NTA
	27	10	6.8	445-2565-1-ND	.24	2.21	17.01	445-2565-2-ND	4,000	95.00/M	AVRL161A1R1NTB
				445-2566-1-ND	.24	2.21	17.01	445-2566-2-ND	4,000	95.00/M	AVRL161A3R3FTA
			6.8	445-2567-1-ND	.24	2.21	17.01	—	—	—	AVRL161A6R8GTA

# VISHAY BC Components Leaded Varistors

The varistors consist of a disc of low-B ceramic material with two tinned solid copper leads. They are coated with a layer of ochre colored epoxy, which provides electrical, mechanical and climatic protection. The encapsulation is resistant to all cleaning solvents in accordance with "IEC 60068-2-45".

Size Code	Maximum Continuous Volt.		Varistor Voltage @ 1mA (V)	Maximum Voltage Stated Current		Dimensions - mm						Digi-Key Part No.	Price Each			Vishay Part No.	
	AC (V)	DC (V)		V	I (A)	D Max.	A Max.	L Min.	T Max.	T Min.	C		F	1	10		100
C	140	180	220	370	25.0	13.5	15.5	17.0	7.0	4.4	0.8 ±0.05	7.5 ±0.8	BC1428-ND	.46	.39	.33	2322 594 51416
	230	300	360	600	25.0	13.5	15.5	17.0	7.0	4.4	0.8 ±0.05	7.5 ±0.8	BC1431-ND	.46	.39	.33	2322 594 52316
D	140	180	220	370	50.0	17.0	19.0	16.0	7.0	4.4	0.8 ±0.05	7.5 ±0.8	BC1449-ND	.59	.51	.42	2322 595 51416
	320	420	510	850	50.0	17.0	19.0	16.0	7.0	4.4	0.8 ±0.05	7.5 ±0.8	BC1456-ND	.59	.51	.42	2322 595 53216



Digi-Reel® Most SMT cutdown parts are available on a Digi-Reel®. For Digi-Reel part number, change 1-ND to 6-ND or CT-ND to DKR-ND. See Digi-Key® Services on page 2 for additional information.

More Product Available Online: [www.digikey.com](http://www.digikey.com)

Toll-Free: 1-800-344-4539 • Phone 218-681-6674 • Fax: 218-681-3380