



# Richco Cable Clamps — N Series


- Features:**  
 • Material: Nylon 6/6, RMS-01  
 • Colors: Natural and Black



Description	Dimensions (mm)		Digi-Key Part No.	Pricing			Richco Part No.
	D	E		25	100	1,000	
Black, RMS-49	1.60	6.86	RP322-ND	1.80	6.16	36.94	N-1-BK
	3.18	8.33	RP323-ND	1.83	6.28	37.69	N-2-BK
	4.78	9.91	RP324-ND	2.10	7.21	43.24	N-3-BK
	6.35	10.69	RP325-ND	2.19	7.49	44.96	N-4-BK
	7.95	11.51	RP326-ND	2.21	7.58	45.47	N-5-BK
	9.52	12.29	RP327-ND	2.40	8.22	49.32	N-6-BK
	11.13	11.99	RP328-ND	2.49	8.53	51.19	N-7-BK
	12.70	14.27	RP329-ND	2.52	8.63	51.77	N-8-BK
Natural, RMS-01	1.60	6.86	RP314-ND	2.00	6.85	41.08	N-1
	3.18	8.33	RP315-ND	2.04	6.98	41.90	N-2
	4.78	9.91	RP316-ND	2.33	8.00	48.02	N-3
	6.35	10.69	RP317-ND	2.43	8.32	49.90	N-4
	7.95	11.51	RP318-ND	2.46	8.42	50.54	N-5
	9.52	12.29	RP319-ND	2.67	9.14	54.83	N-6
	11.13	11.99	RP320-ND	2.77	9.48	56.98	N-7
	12.70	14.27	RP321-ND	2.79	9.58	57.49	N-8

## Hanking Ties

- Features:**  
 • Wrap electrical cords for shipping and packaging  
 • Material: Polyethylene  
 • Color: Natural



Max. Bundle Diameter (mm)	Dimensions (mm)		Digi-Key Part No.	Price Per Package		Richco Part No.
	A	B		100	1,000	
.9 (22.86)	3.2 (81.28)	3.9 (99.06)	RP701-ND	23.13	138.78	HT-3.9
1.4 (35.56)	5.2 (132.08)	5.9 (149.86)	RP703-ND	29.06	174.38	HT-5.9

• RoHS Compliant

## Wrap-It-Ties

- Features:**  
 • Easy to use permanent lock  
 • Strong, one-piece construction  
 • Serviceable to 185°F (85°C)  
 • UL recognized #E71558



RPWTA-ND ..... \$13.59

RPWTD-ND ..... \$59.40

† Replace □ with "C" for package of 100, "M" for package of 1,000.

Max. Bundle Diameter (in.)	Approx. Length (in.)	Min. Loop Tensile Strength (lbs.)	Approx. Width (in.)	Color	Digi-Key Part No.†	Package Size			Richco Part No.
						Price Per Pkg. C = 100	Price Per Pkg. M = 1,000		
<b>Nylon 6/6</b>									
0.6	3.25	18	.10	Natural	RP101□-ND	2.89	16.52		WIT-18SF
0.6	3.25	18	.10	Red	RP101RD-ND	—	18.07		WIT-18SF-RD
0.7	4.5	18	.10	Natural	RP102□-ND	3.22	18.36		WIT-18R
0.7	4.5	18	.10	Blue	RP102BL□-ND	3.29	18.76		WIT-18R-BL
0.7	4.5	18	.10	Green	RP102GN□-ND	4.89	18.76		WIT-18R-GN
0.7	4.5	18	.10	Red	RP102RD□-ND	3.29	18.76		WIT-18R-RD
0.7	4.5	18	.10	Yellow	RP102YL□-ND	3.29	18.76		WIT-18R-YL
1.3	5.75	18	.10	Natural	RP213□-ND	3.86	22.03		WIT-18L
2.1	8.0	18	.10	Natural	RP103□-ND	5.01	28.66		WIT-18V
1.2	5.75	30	.14	Natural	RP104□-ND	6.04	34.52		WIT-30R
1.2	5.75	30	.14	Blue	RP104BL□-ND	—	35.24		WIT-30R-BL
1.2	5.75	30	.14	Green	RP104GN□-ND	9.00	35.24		WIT-30R-GN
1.2	5.75	30	.14	Red	RP104RD□-ND	5.87	35.24		WIT-30R-RD
1.2	5.75	30	.14	Yellow	RP104YL□-ND	6.17	35.24		WIT-30R-YL
1.8	7.3	30	.14	Natural	RP105□-ND	6.49	37.08		WIT-30L
1.8	7.3	30	.14	Green	RP105GN□-ND	9.62	—		WIT-30L-GN
1.8	7.3	30	.14	Yellow	RP105YL□-ND	7.16	—		WIT-30L-YL
0.7	4.5	40	.14	Natural	RP214□-ND	5.98	34.74		WIT-40S
1.2	5.75	40	.14	Natural	RP106□-ND	7.01	40.03		WIT-40R
1.2	5.75	40	.14	Blue	RP106BL□-ND	7.70	39.10		WIT-40R-BL
1.2	5.75	40	.14	Green	RP106GN□-ND	—	39.10		WIT-40R-GN
1.2	5.75	40	.14	Yellow	RP106YL□-ND	7.70	35.60		WIT-40R-YL
1.8	7.3	40	.14	Natural	RP107□-ND	8.74	49.93		WIT-40L
1.8	7.3	40	.14	Green	RP107GN□-ND	9.59	48.71		WIT-40L-GN
1.8	7.3	40	.14	Red	RP107RD□-ND	9.59	48.71		WIT-40L-RD
3.1	11.1	40	.15	Natural	RP215□-ND	15.17	86.65		WIT-40VL
1.5	6.0	50	.19	Natural	RP108□-ND	7.13	40.75		WIT-50S
1.5	6.0	50	.19	Red	RP108RD□-ND	7.84	—		WIT-50S-RD
1.5	6.0	50	.19	Yellow	RP108YL□-ND	10.69	—		WIT-50S-YL
2.0	8.0	50	.19	Natural	RP109□-ND	8.09	46.26		WIT-50R
2.0	8.0	50	.19	Blue	RP109BL□-ND	8.44	48.20		WIT-50R-BL
2.0	8.0	50	.19	Green	RP109GN□-ND	8.44	48.20		WIT-50R-GN
2.0	8.0	50	.19	Red	RP109RD□-ND	12.31	48.20		WIT-50R-RD
2.0	8.0	50	.19	Yellow	RP109YL□-ND	8.44	48.20		WIT-50R-YL
4.5	15.3	50	.18	Natural	RP110□-ND	14.46	82.62		WIT-50L
2.7	10.7	60	.18	Natural	RP216□-ND	12.47	71.24		WIT-60R
4.2	15.06	120	.30	Natural	RP111□-ND	39.43	—		WIT-120R-C
<b>UV Stabilized Nylon 6/6 - Exterior or Outdoor Use</b>									
0.6	3.25	18	.10	Black	RP201□-ND	3.22	18.36		WIT-18SF-UVB
0.7	4.5	18	.10	Black	RP202□-ND	3.53	20.20		WIT-18R-UVB
1.1	8.0	18	.10	Black	RP203M-ND	—	31.21		WIT-18V-UVB
2.1	5.75	30	.14	Black	RP204□-ND	6.68	38.20		WIT-30R-UVB
1.8	7.3	30	.14	Black	RP205□-ND	7.20	41.11		WIT-30L-UVB
1.2	5.75	40	.14	Black	RP206□-ND	8.24	44.06		WIT-40R-UVB
1.8	7.3	40	.14	Black	RP207□-ND	9.58	54.72		WIT-40L-UVB
1.5	6.0	50	.19	Black	RP208□-ND	7.84	44.78		WIT-50S-UVB
2.0	8.0	50	.19	Black	RP209□-ND	8.93	51.05		WIT-50R-UVB

Max. Bundle Diameter (in.)	Approx. Length (in.)	Min. Loop Tensile Strength (lbs.)	Approx. Width (in.)	Color	Digi-Key Part No.	Package Size		Richco Part No.	
						Price Per Pkg. C = 100	Price Per Pkg. M = 1,000		
4.5	15.3	50	.18	Black	RP210□-ND	15.94	91.08	WIT-50L-UVB	
4.2	15.06	120	.30	Black	RP211C-ND	37.08	—	WIT-120R-UVB	
<b>Nylon 6/6, Size 10 — Screw Mount</b>									
1.5	6.75	50	.19	Natural	RP224M-ND	—	94.00	WITSH-10-50MS	
2	8.69	50	.19	Natural	RP225M-ND	—	109.08	WITSH-10-50MRL	
3	11.25	50	.19	Natural	RP226M-ND	—	112.36	WITSH-10-50MR	
<b>Nylon 6/6, Release Tab</b>									
1.25	5.5	40	.21	Natural	RP217M-ND	—	87.98	WIT-RT-0550	
2	8.0	40	.21	Natural	RP218□-ND	16.97	96.98	WIT-RT-0800	
2.5	10.5	40	.21	Natural	RP219□-ND	29.75	146.59	WIT-RT-1050	

Max. Bundle Diameter (in.)	Approx. Length (in.)	Min. Loop Tensile Strength (lbs.)	Approx. Width (in.)	Color	Digi-Key Part No.	Pricing		Richco Part No.
						25	100	
<b>Nylon 6/6, Release Tab (Large Size)</b>								
4	15.25	250	.52	Natural	RP221-ND	40.41	138.56	WIT-RT-1525
6	21.5	250	.52	Natural	RP222-ND	46.20	158.39	WIT-RT-2150
8	27.75	250	.52	Natural	RP223-ND	54.32	186.24	WIT-RT-2775

## Beaded Ties

- Features:** • Easy to install and release • Material: Nylon 6/6 • Color: Natural





Fig.	Dim "A" (approx.) Inch (mm)	Digi-Key Part No.	Price Per Package		Richco Part No.
			100	1,000	
1	4.0 (101.60)	RP731-ND	9.19	55.15	BT-4-01-NT
	6.0 (152.40)	RP733-ND	16.06	96.34	BT-6-01-NT
2	8.75 (222.25)	RP734-ND	22.24	133.45	BT-8-01-NT
	10.75 (273.05)	RP735-ND	27.76	166.54	BT-10-01-NT
	12.75 (323.85)	RP736-ND	31.67	190.01	BT-12-01-NT

## Molded Nylon Insulators — MNI Series

- Features:** • Use as screw insulators and in many bushing applications  
 • Lightweight • High dielectric strength • Resistant to corrosion and abrasion • Material: Nylon 6/6, RMS-48 • Color: Natural



Max. Bundle Diameter (in.)	Approx. Length (in.)	Min. Loop Tensile Strength (lbs.)	Approx. Width (in.)	Color	Digi-Key Part No.†	Package Size			Richco Part No.		
						Price Per Pkg. C = 100	Price Per Pkg. M = 1,000				
<b>Nylon 6/6</b>											
#2	M2.2	.181	.047	.120	.090	.031	RP330-ND	6.07	20.80	124.81	MNI#2-2
#4	M3	.235	.047	.145	.115	.031	RP337-ND	6.07	20.80	124.81	MNI#4-2
		.252	.047	.140	.115	.046	RP338-ND	6.07	20.80	124.81	MNI#4-3
		.235	.047	.145	.115	.063	RP339-ND	6.07	20.80	124.81	MNI#4-4
		.252	.047	.140	.115	.084	RP340-ND	6.07	20.80	124.81	MNI#4-5
		.252	.047	.140	.115	.093	RP341-ND	6.07	20.80	124.81	MNI#4-6
		.235	.047	.145	.115	.125	RP342-ND	6.07	20.80	124.81	MNI#4-8
#5	M3	.252	.047	.140	.115	.156	RP343-ND	6.07	20.80	124.81	MNI#4-10
		.235	.047	.145	.115	.187	RP344-ND	6.07	20.80	124.81	MNI#4-12
		.252	.047	.140	.115	.250	RP345-ND	6.07	20.80	124.81	MNI#4-16
		.235	.047	.145	.115	.375	RP346-ND	6.07	20.80	124.81	MNI#4-24
		.370	.050	.236	.126	.050	RP347-ND	7.28	24.97	149.83	MNI#5-3
		.290	.047	.170	.140	.031	RP348-ND	6.08	20.84	125.03	MNI#6-2
#6	M3.5	.290	.047	.170	.140	.093	RP350-ND	6.08	20.84	125.03	MNI#6-6
		.290	.047	.170	.140	.125	RP351-ND	6.08	20.84	125.03	MNI#6-8
		.290	.047	.170	.140	.187	RP352-ND	6.08	20.84	125.03	MNI#6-12
		.300	.047	.170	.138						