




Miniature Display D.C. Voltmeter



MDMV Series: SPECIFICATIONS: • Display: 3-1/2-digit, 0.4" (10.2mm) high digits. A minus (-) sign is displayed when voltage is negative • Decimal Points: Selectable decimal points are activated at the rear terminal pins to allow the display to be read in tenths, hundredths or thousandths • Annunciators: 5 selectable annunciators, BAT, V, A, μ and m are activated at the appropriate rear terminal • Power Requirements: 4.8VDC – 6VDC @ 5mA Maximum • Input Range: 0 to \pm 199.9m VDC • Over-range Indication: Over-range is indicated by a "1" displayed in the most significant digit and the blanking of the three least significant digits • Reading Rate: 2 1/2 readings per second • Common Mode Rejection Ratio: 70dB • Input Impedance: 1000M Ω • Operating Range: 0°C – 60°C


CUB4V Series: SPECIFICATIONS: • LCD, positive reflective or negative transmissive with yellow/green or red backlighting • Four selectable D.C. ranges (0-199.9 mV, 1.999 V, 19.99 V, 199.9 V) • 0.6" (15.24mm) high LCD digits • Built-in scaling provided • Auto-zeroing circuit • Selectable decimal points • Wire connections made via screw clamp type terminals • Fits DIN standard cut-out 2.68" (68mm) x 1.30" (33mm) • NEMA 4X/IP65 sealed front panel bezel • 9 – 28VDC powered

| Description | Digi-Key Part No. | Price Each | | Red Lion Part No. |
|---|-------------------|------------|-------|-------------------|
| | | 1 | 5 | |
| MDMV Series | | | | |
| Panel Mt., Reflective Display | RLC000-ND | 40.80 | 39.78 | MDMV0000 |
| Panel Mt., Ylw./Grn. Backlight Display | RLC010-ND | 53.60 | 52.26 | MDMV0010 |
| Panel Mt., Red Backlight Display | RLC020-ND | 53.60 | 52.26 | MDMV0020 |
| PC Board Mt., Reflective Display | RLC100-ND | 37.60 | 36.66 | MDMV0100 |
| PC Board Mt., Ylw./Grn. Backlight Display | RLC110-ND | 51.20 | 49.92 | MDMV0110 |
| PC Board Mt., Red Backlight Display | RLC120-ND | 51.20 | 49.92 | MDMV0120 |
| MDM Cable Assembly | RLC70-ND | 14.04 | 13.69 | HWK70000 |
| CUB4V Series — RoHS Compliant | | | | |
| DC Voltmeter | RLC4V0-ND | 104.00 | — | CUB4V000 |
| DC Voltmeter, Ylw./Grn. Backlight Display | RLC4V1-ND | 115.44 | — | CUB4V010 |
| DC Voltmeter, Red Backlight Display | RLC4V2-ND | 115.44 | — | CUB4V020 |

RoHS Compliant

LD Series Large Display Counters and Timers


Red Lion's low cost large digit displays are available in either large 2.25" (57.15mm) red LED digit height or very large 4.0" (101.60mm) red LED digit height. Choose either a single counter function or single timer function that is housed in a NEMA 4 case construction and features adjustable brightness control, 85 – 250VAC power input and selectable high or low frequency (0.01 Hz – 35kHz) inputs. Perfect for industrial settings such as factory displays, outside displays or long distance displays.



| Description | Dimension - Inch (mm) | | Digi-Key Part No. | Price Each | Red Lion Part No. |
|--|-----------------------|---------------|-------------------|------------|-------------------|
| | X | Y | | | |
| 4.0" (101.60mm) High 4 Digit Red LED Counter, 120VAC | 20.0 (508.0) | 7.875 (200.0) | RLC118-ND | 504.40 | LD400400 |
| 4.0" (101.60mm) High 6 Digit Red LED Timer, 120VAC | 26.0 (660.4) | 7.875 (200.0) | RLC125-ND | 660.40 | LD4T06P0 |

PAX Lite Meters

Dimensions in inches



PAX LITE DC Current and Voltmeters



PAX Lite Current and Volt Meters are premium quality instruments designed for tough industrial applications. With multi-range capability, built-in provision for scaling, and DIP switch selectable decimal points, these meters offer the ultimate in application flexibility. Two models cover your voltage and current indicator needs. The meter can provide direct readout from pressure, speed or flow transducers, or any other variable that can be translated to voltage or current. The built-in scaling allows the display to be scaled to the desired engineering unit.

Specifications: • Power: 115/230VAC, switch selectable, 50/60 Hz • Input Ranges/Resolution: Selectable by jumper connections • Accuracy: • DC Voltmeters: 1 mV, 10 mV, 100 mV or 1 V • DC Current Meters: 199.9 μ A/199.9 mA, 1.999 mA, 19.99 mA or 1.999 A • Over-Range Indication: on all modes is indicated by blanking 3 least significant digits

| | |
|--|----------|
| RLC105-ND (PAXLID00) PAX LITE DC Current, 3 1/2-Digit, LED Meter | \$109.20 |
| RLC107-ND (PAXLVD00) PAX LITE DC Voltmeter, 3 1/2-Digit, LED Meter | \$109.20 |

PAX LITE 600 VAC Voltage Monitor



The Model PAXLHV is designed for AC voltage monitoring. The half-wave rectified input signal is calibrated to indicate the RMS value of a pure sinusoidal wave-form. The front bezel meets NEMA 4X/IP65 requirements when properly installed.

Specifications: • Power: 115/230VAC, switch selectable, 50/60 Hz • Input Range: 0 – 600VAC maximum • Resolution: 1VAC • Operating Temperature Range: 0°C – 60°C • Reading Rate: 400 msec., nominal • Response Time: 1 second nominal for a step change input

| | |
|---|----------|
| RLC111-ND (PAXLHV00) AC Voltage Monitor, 3-Digit, LED Meter | \$154.96 |
|---|----------|

PAX LITE 5A AC Current Meter



PAX LITE 5 Amp AC Current Meter provides the capability of measuring large AC currents. The internal current shunt in the PAXLIT can measure up to 5 Amps AC current directly. Using an external current transformer, AC currents of up to 1,999 Amps can be measured and displayed. The PAXLIT can be scaled, using the scaling potentiometer to display between 200 and 1999 when measuring full scale current. Using the DIP switch selectable decimal points, the display can be customized for direct readout for practically any application

Specifications: • Display: 3 1/2-digit, 0.56" (14.2 mm) high, 7-segment LED; Decimal points inserted before 1st, 2nd, or 3rd least significant digits by DIP switch selection. • Power: 115/230VAC, switch selectable, 50/60 Hz • Range: 0 – 5 Amps AC @ 45 – 400 Hz • Accuracy: \pm (0.5% of reading + 5 digits) • Over-Range Indication: indicated by blanking 3 least significant digits • Maximum Shunt Current: 50 Amps for 1 second; 8 Amps continuous • Operating Temperature: 0°C – 60°C

| | |
|--|----------|
| RLC109-ND (PAXLIT00) PAX LITE Large AC Current, 3 1/2-Digit, LED Meter | \$154.96 |
|--|----------|

PAX LITE Counter

The PAX Lite Counter, Model PAXLC, is a versatile totalizing counter that can be adapted to a wide variety of counting, measuring and positioning readout applications. The unit features a programmable scale factor, front panel and remote reset, store, inhibit and a count rate of 25 kHz, while offering an economical solution to any totalizing need. The PAXLC accepts digital inputs from a variety of sources including switch contacts, NPN-OC and TTL outputs, as well as most standard Red Lion sensors. The input can be scaled to display any desired unit of measure by simply using the programmable scale factor.

Specifications: • Overflow indicated by flashing dot to the right of digit. Decimal points are programmed by front panel keys. • AC Power: 115/230VAC, switch selectable, 50/60 Hz • DC Power: 10 – 16VDC @ 0.1 A maximum • Keypad: 3 programming keys, the (Down Arrow) key can also function as the front panel reset button • Count Input: DIP switch selectable, • Filter: Damping capacitor provided for switch contact bounce. Limits input frequency to 50 Hz and input pulse widths to 10 msec. minimum • Maximum Count Rate: 25 kHz maximum

| | |
|---|----------|
| RLC102-ND (PAXLC800) PAX LITE Counter, 8-Digit, LED Meter | \$157.04 |
|---|----------|

PAX LITE Rate Meter



The PAX Lite Rate Meter, Model PAXLR, provides the versatility and flexibility needed to accommodate virtually any rate measuring application. The meter has the ability to scale for direct readout in terms of the units being measured. Whether a machine produces bottles, cloth, wire or beverage mix, operation is enhanced when the rate readout is expressed directly in bottles/minute, feet/minute, gallons/minute or whatever units are needed in plant applications. The PAXLR can accommodate magnetic pickups, logic sensors and NPN open collector sensors. The meter is programmed through both the front panel buttons and DIP switches. Once the programming is complete, the front panel buttons can be disabled by a DIP switch setting.

Specifications: • Decimal points are programmed by front panel keys. • AC Power: 115/230VAC, switch selectable, 50/60 Hz • DC Power: 10 – 16VDC @ 0.1 A maximum • Keypad: 3 programming keys; Outputs, Magnetic Pickups and all standard Red Lion sensors • Input Frequency Range: • Maximum Frequency: 25 kHz • Minimum Frequency: 0.01 Hz • Accuracy: \pm 0.01% • Memory: Nonvolatile E2PROM retains all programmable parameters and display values. • Operating Temperature: 0°C – 60°C

| | |
|--|----------|
| RLC103-ND (PAXLR000) PAX LITE Rate, 6-Digit, LED Meter | \$148.72 |
|--|----------|

PAX LITE Process Time Meter



The PAX Lite Process Time Meter, Model PAXLPT, displays a value representing the time between a beginning and end point of a process, such as a conveyor oven. The PAXLPT's display will update inversely in relation to the input signal frequency. As input frequency increases (representing speed), the PAXLPT time display will decrease indicating a reduction in the duration of process time. For example, the bake time through an oven will decrease the faster the conveyor runs. The display can be programmed for two operating modes. Operating in the 6 digit mode, the PAXLPT can readout in any whole value, such as seconds, minutes or hours. This mode also provides capability for decimal points. The 5 digit mode functions as a chronometer, which has a maximum display value of 999.59. This formats the display to allow the meter to readout in hours and minutes, minutes and seconds, etc.

Specifications: • AC Power: 115/230VAC, switch selectable, 50/60 Hz • DC Power: 10 – 16VDC @ 0.1 A maximum • Keypad: 3 programming keys • Input: DIP switch selectable; accepts pulses from a variety of sources including NPN-OC, PNP-OC, TTL Outputs, Magnetic Pickups and all standard Red Lion sensors. • Maximum input voltage: \pm 40 V peak, 30 Vrms • Input Frequency Range: • Maximum frequency: 25 kHz • Minimum frequency: 0.05 Hz • Accuracy: \pm 0.02% • Memory: Nonvolatile E2PROM retains all programmable parameters. • Operating Temperature: 0°C – 60°C

| | |
|--|----------|
| RLC104-ND (PAXLPT00) PAX LITE Process Time, 6-Digit, LED Meter | \$227.67 |
|--|----------|

PAX LITE Current Loop Meter



With its high sensitivity and programmability, the PAX Lite Current Loop Meter can be set up for a wide variety of applications. In most plants the PAXLCL can be used for 90 to 95% of current loop meter needs for readout of pressure, flow, temperature, level and other variables. The meter has been specifically designed for harsh industrial environments.

Specifications: • Over-Range Indication: Indicated by blanking 3 least significant digits • Power: AC Power: 85 – 250VAC, 50/60 Hz, 6VA • Isolation: 2300 Vrms for 1 minute between input and supply (300V working voltage) • Input Sensitivity: (Numerical Readout Change/mA) 260 units/mA @ 4 – 20 mA input, 105 units/mA @ 10 – 50 mA input (maximum allowable input current, 170 mA) • Input Resistance: 4 – 20 mA – 29.2 Ω , 10 – 50 mA – 11.8 Ω . • Span: 32 coarse steps (binary progression with 5 DIP switches) Each step providing approximately 8.125 numerical units/mA/step sensitivity for 4 – 20 mA input and 3.25 units/mA/step for 10 to 50 mA input.

| | |
|--|----------|
| RLC112-ND (PAXLCL00) PAX LITE Current Loop, 3 1/2-Digit, LED Meter | \$154.96 |
|--|----------|

PAX LITE RTD Meter

The PAX Lite RTD Meter accepts standard RTD inputs and precisely linearizes them into temperature readings. A full 4-digit display accommodates a wide range of temperature inputs. State-of-the-art digital circuitry virtually eliminates errors due to drift. The meter features a readout choice of either Fahrenheit or Celsius with 0.1 or 1 degree resolution. English Style display prompts and front panel buttons aid the operator through set-up and operation.

Specifications: • Power: 85 – 250VAC, 50/60 Hz • Controls: Three front panel push buttons for meter set-up; rear terminal input for disabling the front panel • Resolution: 0.1 or 1 degree • Range: Decimal Point Dependent 0.1° res: -199.9°C – 850.0°C (-199.9°F – 999.9°F); 1° res: -200°C – 850°C (-328°F – 1562°F) • Open/Shorted RTD Detection: Display flashes: "LOL" or "OLL" • Accuracy: 0.3°C, @ 23°C and 30 minutes warm-up • Reading Rate: 2.5 readings/second • Response Time: 2 seconds to settle for step input (increases with programmable digital filtering) • Low Frequency Noise Rejection: Normal Mode Rejection: 40 dB @ 50/60 Hz (may be improved by programmable digital filtering) • Common Mode Rejection: 120 dB, DC to 50/60 Hz. • Operating Temperature Range: 0°C – 50°C

| | |
|---|----------|
| RLC115-ND (PAXLRT00) PAX LITE RTD, 4-Digit, LED Meter | \$193.44 |
|---|----------|

More Product Available Online: www.digikey.com

Toll-Free: 1-800-344-4539 • Phone 218-681-6674 • Fax: 218-681-3380

(T091) 2539

PRD Plastics


Bezels

- Bezel material is polystyrene plastic
- Recommended panel thickness for mounting snap-fit bezel is .813mm - 3.18mm



| Digi-Key Part No. | Dimensions (mm) | | Panel Cut-Out For Snap Fit Bezel | |
|-------------------|-----------------|-------|----------------------------------|-------|
| | A | B | Height | Width |
| PRD180B-ND | 58.74 | 45.72 | 26.99 | 52.39 |
| PRD250B-ND | 76.20 | 63.50 | 26.99 | 69.85 |
| PRD360B-ND† | 104.78 | 91.44 | 26.99 | 98.43 |

† PRD360B-ND has 4 snap-on plastic clip bars



| Description | Digi-Key Part No. | Price Each | | | PRD Plastics Part No. |
|--|-------------------|------------|------|------|-----------------------|
| | | 1 | 10 | 100 | |
| Snap Fit Bezels (Lenses Must Be Ordered Separately) | | | | | |
| 45.72mm Wide Bezel Black Plastic..... | PRD180B-ND | 1.71 | 1.43 | 1.14 | 6101010 |
| 63.50mm Wide Bezel Black Plastic..... | PRD250B-ND | 2.10 | 1.75 | 1.40 | 6102010 |
| 91.44mm Wide Bezel Black Plastic..... | PRD360B-ND | 2.46 | 2.05 | 1.64 | 6103010 |
| For Use With LCDs | | | | | |
| Clear Lens for 45.72mm Bezel..... | PRD180C-ND | 1.53 | 1.28 | 1.02 | 6201010 |
| Clear Lens for 63.50mm Bezel..... | PRD250C-ND | 1.71 | 1.43 | 1.14 | 6202010 |
| Clear Lens for 91.44mm Bezel..... | PRD360C-ND | 1.92 | 1.60 | 1.28 | 6203010 |
| For Use With LEDs | | | | | |
| Smoke Lens for 45.72mm Bezel..... | PRD180S-ND | 1.53 | 1.28 | 1.02 | 6201020 |
| Smoke Lens for 63.50mm Bezel..... | PRD250S-ND | 1.71 | 1.43 | 1.14 | 6202020 |
| Smoke Lens for 91.44mm Bezel..... | PRD360S-ND | 1.92 | 1.60 | 1.28 | 6203020 |
| Red Lens for 45.72mm Bezel..... | PRD180R-ND | 1.53 | 1.28 | 1.02 | 6201030 |
| Red Lens for 63.50mm Bezel..... | PRD250R-ND | 1.71 | 1.43 | 1.14 | 6202030 |
| Red Lens for 91.44mm Bezel..... | PRD360R-ND | 1.92 | 1.60 | 1.28 | 6203030 |
| Green Lens for 45.72mm Bezel..... | PRD180G-ND | 1.53 | 1.28 | 1.02 | 6201040 |
| Green Lens for 63.50mm Bezel..... | PRD250G-ND | 1.71 | 1.43 | 1.14 | 6202040 |
| Green Lens for 91.44mm Bezel..... | PRD360G-ND | 1.92 | 1.60 | 1.28 | 6203040 |
| Masked Lenses | | | | | |
| 25.40mm x 22.23mm Window for 45.72mm..... | PRD180W-ND | 1.53 | 1.28 | 1.02 | 6201050 |
| 60.96mm x 16.00mm Window for 63.50mm..... | PRD250W-ND | 1.71 | 1.43 | 1.14 | 6202050 |
| 65.41mm x 13.79mm Window for 63.50mm..... | PRD250W1-ND | 1.71 | 1.43 | 1.14 | 6202060 |
| 83.01mm x 18.59mm Window for 91.44mm..... | PRD360W-ND | 1.92 | 1.60 | 1.28 | 6203050 |
| 93.35mm x 15.80mm Window for 91.44mm..... | PRD360W1-ND | 1.92 | 1.60 | 1.28 | 6203060 |



| Description | Digi-Key Part No. | Price Each | | | PRD Plastics Part No. |
|--|-------------------|------------|------|------|-----------------------|
| | | 1 | 10 | 100 | |
| Lo-Profile Polycarbonate/ABS | | | | | |
| Lo-Profile For LCDs * | | | | | |
| 45.72mm Bezel with Clear Lens..... | PRD180LP-ND | 3.39 | 2.83 | 2.26 | 6301010 |
| 45.72mm Bezel with Clear Lens with 25.40mm x 22.23mm Window..... | PRD180LPW-ND | 3.39 | 2.83 | 2.26 | 6301020 |
| 63.50mm Bezel with Clear Lens..... | PRD250LP-ND | 3.81 | 3.18 | 2.54 | 6302010 |
| 63.50mm Bezel with Clear Lens with 60.96mm x 16.00mm Window..... | PRD250LPW-ND | 3.81 | 3.18 | 2.54 | 6302020 |
| 63.50mm Bezel with Clear Lens with 65.41mm x 13.79mm Window..... | PRD250LPW1-ND | 3.81 | 3.18 | 2.54 | 6302030 |
| 91.44mm Bezel with Clear Lens..... | PRD360LP-ND | 4.35 | 3.63 | 2.90 | 6303010 |
| 91.44mm Bezel with Clear Lens with 83.01mm x 18.59mm Window..... | PRD360LPW-ND | 4.35 | 3.63 | 2.90 | 6303020 |
| 91.44mm Bezel with Clear Lens with 93.35mm x 15.80mm Window..... | PRD360LPW1-ND | 4.35 | 3.63 | 2.90 | 6303030 |
| Lo-Profile For LEDs * | | | | | |
| 45.72mm Bezel with Smoke Lens..... | PRD180LPS-ND | 3.39 | 2.83 | 2.26 | 6301040 |
| 45.72mm Bezel with Red Lens..... | PRD180LPR-ND | 3.39 | 2.83 | 2.26 | 6301050 |
| 45.72mm Bezel with Green Lens..... | PRD180LPG-ND | 3.39 | 2.83 | 2.26 | 6301060 |
| 63.50mm Bezel with Smoke Lens..... | PRD250LPS-ND | 3.81 | 3.18 | 2.54 | 6302040 |
| 63.50mm Bezel with Red Lens..... | PRD250LPR-ND | 3.81 | 3.18 | 2.54 | 6302050 |
| 63.50mm Bezel with Green Lens..... | PRD250LPG-ND | 3.81 | 3.18 | 2.54 | 6302060 |
| 91.44mm Bezel with Smoke Lens..... | PRD360LPS-ND | 4.35 | 3.63 | 2.90 | 6303040 |
| 91.44mm Bezel with Red Lens..... | PRD360LPR-ND | 4.35 | 3.63 | 2.90 | 6303050 |
| 91.44mm Bezel with Green Lens..... | PRD360LPG-ND | 4.35 | 3.63 | 2.90 | 6303060 |
| Accessories | | | | | |
| Adhesive Strips 2/Pad..... | PRDAS-ND | .31 | .30 | .28 | 6000010 |

* Requires Adhesive Strips (recommend 2 pads for the 91.44mm Bezel)




Analog Panel Meters

The PB Series was designed to meet the expressed need of many customers for meters with a hard-hitting, big-dial-area "industrial" look.



| Type | Frequency Range | Input V | Accuracy | Digi-Key Part No. | 1 | Price Each 5 | 10 | Jewell Instruments Part No. |
|---|-----------------|---------|----------------|-------------------|--------|--------------|--------|-----------------------------|
| Frequency Meters Pointer Type Electronic | | | | | | | | |
| Square | 45-55Hz | 120VAC | ±.3Hz | 180-1086-ND | 120.00 | 117.00 | 114.00 | R3PB-FRQ-50/120-10-U |
| | 55-65Hz | | | 180-1087-ND | 120.00 | 117.00 | 114.00 | R3PB-FRQ-60/120-10-U |
| Rectangular | 45-65Hz | 120VAC | ±.6Hz ±.3Hz | 180-1068-ND | 120.00 | 117.00 | 114.00 | R3S-FRQ-55/120-20-U |
| | | | | 180-1069-ND | 120.00 | 117.00 | 114.00 | R3S-FRQ-50/120-10-U |

Miniature Backlit 1000 Series



Specifications: Display:

- Digits: 3 1/2 digits (1999) • Digit Height: 0.3" (7.6mm) • Decimal Point: 3 positions, external selection • Type: 7 Segment Backlit LCD • Polarity: Automatic (-) displayed • Overload: Three lower digits blank for readings greater than 1999 • Input: • Full Scale Range: ±2V or ±200m VDC • Input Resistance: ±100MΩ
- Overvoltage Protection: 100VDC or peak AC conditions

Performance:

- Accuracy: = (0.25% + 1 count) Maximum • Common Mode Rejection: ≥ 86db 50Hz-60Hz • Zero Adjust: Automatic • Conversion Rate: 2.5 Per Second
- Tempo: 100 PPM/°C

Environment:

- Operating Range: -0°C - 60°C • Storage Range: -20°C - 70°C • Extended Temperature (option): • Operating Range: -30°C - 80°C • Storage Range: -40°C - 85°C • Power Options: • +5VDC and -5VDC ±10% @ 150ua DC or 9VDC (7.2 - 12VDC isolated @ 150µADC)


Note: For the battery powered DPM, the input must either be fully isolated from the power source, or, if referenced to the source, the IN LO terminal must be no closer than 2.3V for the 200mV range (3.5V for the 2V range) to either battery terminal.

| Display | Mounting | Terminals | DPM Power | Input | Digi-Key Part No. | 1 | Price Each 5 | 10 | Jewell Instruments Part No. |
|--------------------|----------|--------------|--------------|------------|-------------------|--------|--------------|--------|-----------------------------|
| Pos. Red Backlight | Window | with 13 pins | Loop Powered | 4 - 20mADC | 180-1051-ND | 183.10 | 178.53 | 173.95 | 1060-0019-U |

More Product Available Online: www.digikey.com

2540 (T091)

Toll-Free: 1-800-344-4539 • Phone 218-681-6674 • Fax: 218-681-3380




Specifications: Performance: • Conversion Rate: 2.5 per second • Common Mode Rejection: $\geq 100\text{db}$ 50Hz-60Hz • Tempco: $\pm 200\text{PPM}/^\circ\text{C}$ typical except thermocouple inputs which are $1/^\circ$ degree zero tempco for selectable process ranges is only $\pm .2$ count/ $^\circ\text{C}$ • Normal Mode Rejection: $\geq 40\text{db}$ 50Hz-60Hz • Zero Adjust: Automatic • Warmup: 10 minutes **Environment:** • Operating Range: $-4^\circ\text{F} - 140^\circ\text{F}$ ($-20^\circ\text{C} - 60^\circ\text{C}$) • Storage Range: $-22^\circ\text{F} - 150^\circ\text{F}$ ($-30^\circ\text{C} - 70^\circ\text{C}$) • **Power Options:** • 115V + 10%, -15% 50Hz to 400Hz at 2VA • 230V +10%, -15% 50Hz to 400Hz at 2VA • **Backlighting Options:** • Positive Green (Green Background, Black Characters) • Negative Red (Black Background, Red Characters) • **FCC Compliance:** • Complies with the class B limits of FCC rules and regulations, part 15, sub part J for conducted and radiated emissions. • Except isolated DC powered which is $\geq 80\text{db}$ 50Hz-60Hz

| Display | DPM Power | Input† | Backlit Power†† | Digi-Key Part No. | 1 | Price Each 5 | 10 | Modutec Part No. |
|---|---------------|------------------------------|-----------------|-------------------|--------|--------------|--------|------------------|
| TRMS (Power) - Universal Selectable True RMS | | | | | | | | |
| Neg. Red Backlit | 115 or 230VAC | 250VAC | 115 or 230VAC | 180-1036-ND | 256.30 | 249.90 | 243.49 | 2353-1026-10-U |
| Neg. Red Backlit | | 200.0VAC | 115 or 230VAC | 180-1037-ND | 256.30 | 249.90 | 243.49 | 2353-1024-10-U |
| 1/8 DIN | | | | | | | | |
| Neg. Red Backlit | 115VAC | Type J Thermocouple | 115VAC | 180-1040-ND | 76.58 | — | 73.52 | 2053-3480-04-U |
| Neg. Red Backlit | | 100 Ohms Pt 1" Resolution | | 180-1041-ND | 76.58 | — | 73.52 | 2053-3470-04-U |
| Neg. Red Backlit | | 0 - 50AAC Avg | | 180-1042-ND | 144.70 | 141.09 | 137.47 | 2053-3439-04-U |
| Neg. Red Backlit | | 80 - 260VAC Avg | | 180-1043-ND | 144.70 | 141.09 | 137.47 | 2053-3429-04-U |
| Pos. Green Backlit | | 0 - 2VDC scaled 0 to 1.999 | | 180-1046-ND | 144.70 | 141.09 | 137.47 | 2035-3402-04-U |
| Pos. Green Backlit | | 0 - 200mVDC scaled 0 - 199.9 | | 180-1047-ND | 144.70 | 141.09 | 137.47 | 2035-3401-04-U |
| Non Backlit | Loop Power | 4 - 20mA DC scaled 0 - 100.0 | No Backlight | 180-1048-ND | 184.60 | 179.99 | 175.37 | 2013-3019-00-U |

† Rated for use with 5A or 50A external current transformer supplied with DPM. †† Backlight power must be same as selected DPM power.

Big - Little Digital Panel Meters

BL Series Specifications: Display: • Digits: 3 1/2 digits, 7 segments backlit LCD (1999) • Digit Height: 0.5" (12.7mm) • Polarity: Automatic (-) displayed • Decimal Point: Three positions, external selection • Overload: Three lower digits blank for readings greater than 1999 • Low battery: "Low Bat" indicator for $< 7.2\text{V}$ (9V power only) **Performance:** • Accuracy: $\pm (0.1\% \text{ rdg} + 2 \text{ count})$ with + 5 and $\pm 5\text{V}$ power $\pm (0.1\% \text{ rdg} + 1 \text{ count})$ with 9V power 2.5 per second • Conversion Rate: 2.5 per second • Common Mode Voltage Range: $\pm 1\text{V}$ maximum • Common Mode Rejection: $> 86\text{db}$ • Zero Adjust: Automatic • Tempco: 100PPM/ $^\circ\text{C}$ typical **Standard Analog Inputs:** • Full Scale Range: Choice $\pm 200\text{mV}$, $\pm 2\text{V}$, or $\pm 20\text{V}$ (Special ranges and engineering units available) • Configuration: True differential input and references • Ratimetric Operation: Available on models BL-100, -130, -300, -330, -400, -430, -500, -530, -600, and -630 • Protection: 250VDC or 150V RMS continuous 300V intermittent maximum • Bias Current: 1pA typical, 10pA maximum • All backlighting power is + 5VDC



| Display | Mounting | DPM Power | Input | Digi-Key Part No. | 1 | Price Each 5 | 10 | Modutec Part No. |
|---|----------|-----------|-------------|-------------------|--------|--------------|-------|------------------|
| Fig. 1 — 13 Pin Terminals Backlit Power 5VDC | | | | | | | | |
| Negative Red Backlit | Bezel | +5VDC | 0 - 2VDC | 180-1002-ND | 102.70 | 100.14 | 97.57 | BL-530302-01-U |
| | Bezel | +5VDC | 0 - 200mVDC | 180-1003-ND | 102.70 | 100.14 | 97.57 | BL-530301-01-U |
| | Window | +5VDC | 0 - 2VDC | 180-1004-ND | 98.50 | 96.04 | 93.58 | BL-500302-01-U |
| | Window | +5VDC | 0 - 200mVDC | 180-1005-ND | 98.50 | 96.04 | 93.58 | BL-500301-01-U |
| | Window | 9VDC | 0 - 2VDC | 180-1006-ND | 98.50 | 96.04 | 93.58 | BL-500102-01-U |
| | Window | 9VDC | 0 - 200mVDC | 180-1007-ND | 98.50 | 96.04 | 93.58 | BL-500101-01-U |
| Negative Green Backlit | Window | +5VDC | 0 - 2VDC | 180-1008-ND | 95.70 | 93.31 | 90.92 | BL-400302-01-U |
| | Window | +5VDC | 0 - 200mVDC | 180-1009-ND | 95.70 | 93.31 | 90.92 | BL-400301-01-U |
| | Window | 9VDC | 0 - 2VDC | 180-1010-ND | 95.70 | 93.31 | 90.92 | BL-400102-01-U |
| | Window | 9VDC | 0 - 200mVDC | 180-1011-ND | 95.70 | 93.31 | 90.92 | BL-400101-01-U |
| Positive Green Backlit | Bezel | +5VDC | 0 - 2VDC | 180-1012-ND | 95.70 | 93.31 | 90.92 | BL-330302-01-U |
| | Bezel | +5VDC | 0 - 200mVDC | 180-1013-ND | 95.70 | 93.31 | 90.92 | BL-330301-01-U |
| | Window | +5VDC | 0 - 2VDC | 180-1014-ND | 91.50 | 89.22 | 86.93 | BL-300302-01-U |
| | Window | +5VDC | 0 - 200mVDC | 180-1015-ND | 91.50 | 89.22 | 86.93 | BL-300301-01-U |
| Standard Reflective LCD | Window | 9VDC | 0 - 2VDC | 180-1016-ND | 91.50 | 89.22 | 86.93 | BL-300102-01-U |
| | Window | 9VDC | 0 - 200mVDC | 180-1017-ND | 91.50 | 89.22 | 86.93 | BL-300101-01-U |
| | Bezel | +5VDC | 0 - 20VDC | 180-1021-ND | 77.50 | 75.57 | 73.63 | BL-130303-U |
| | Bezel | +5VDC | 0 - 2VDC | 180-1022-ND | 69.00 | 67.28 | 65.55 | BL-130302-U |
| | Bezel | +5VDC | 0 - 200mVDC | 180-1023-ND | 77.50 | 75.57 | 73.63 | BL-130301-U |
| | Window | +5VDC | 0 - 20VDC | 180-1024-ND | 73.30 | 71.47 | 69.64 | BL-100303-U |
| Standard Reflective LCD | Window | +5VDC | 0 - 2VDC | 180-1025-ND | 73.30 | 71.47 | 69.64 | BL-100302-U |
| | Window | +5VDC | 0 - 200mVDC | 180-1026-ND | 73.30 | 71.47 | 69.64 | BL-100301-U |
| | Window | 9VDC | 0 - 2VDC | 180-1027-ND | 73.30 | 71.47 | 69.64 | BL-100102-U |
| | Window | 9VDC | 0 - 200mVDC | 180-1028-ND | 73.30 | 71.47 | 69.64 | BL-100101-U |
| Fig. 2 — Flat Pack | | | | | | | | |
| Standard Reflective LCD | Window | +5VDC | 20VDC | 180-1018-ND | 64.70 | 63.09 | 61.47 | BL-176303-U |
| | Window | +5VDC | 2VDC | 180-1019-ND | 64.70 | 63.09 | 61.47 | BL-176302-U |
| | Window | +5VDC | 200mVDC | 180-1020-ND | 64.70 | 63.09 | 61.47 | BL-176301-U |
| Bezel Kit | — | — | — | 180-1001-ND | 10.00 | 9.75 | 9.50 | 176-BK-U |

◆ RoHS Compliant

NEW! **Murata Power Solutions** **Digital Panel Meters** Formerly **DATTEL**



| Series | Display | DPM Power | Input Range | Dimensions - mm (Inch) | Digi-Key Part No. | 1 | Price Each 10 | 50 | Murata Part No. |
|--|------------------------|--------------------|-------------------------|-------------------------|-------------------|-------|---------------|-----------------|------------------|
| 3 1/2 Digit, Digital Panel Meters | | | | | | | | | |
| DMS-20PC | Standard Red LED | +5VDC | $\pm 200\text{mV}$ | 35.1 (1.38) 22.4 (0.88) | 811-1000-ND | 42.19 | 39.72 | 38.48 | DMS-20PC-0-RS-C |
| | | +5VDC | $\pm 2\text{V}$ | 35.1 (1.38) 22.4 (0.88) | 811-1001-ND | 42.19 | 39.72 | 38.48 | DMS-20PC-1-RS-C |
| | | +5VDC | $\pm 20\text{V}$ | 35.1 (1.38) 22.4 (0.88) | 811-1002-ND | 42.19 | 39.72 | 38.48 | DMS-20PC-2-RS-C |
| | Low-Power Red LED | +5VDC | $\pm 200\text{mV}$ | 35.1 (1.38) 22.4 (0.88) | 811-1003-ND | 46.22 | 43.51 | 42.15 | DMS-20PC-0-RL-C |
| | | +5VDC | $\pm 2\text{V}$ | 35.1 (1.38) 22.4 (0.88) | 811-1004-ND | 46.22 | 43.51 | 42.15 | DMS-20PC-1-RL-C |
| | | +5VDC | $\pm 20\text{V}$ | 35.1 (1.38) 22.4 (0.88) | 811-1005-ND | 46.22 | 43.51 | 42.15 | DMS-20PC-2-RL-C |
| | High-Intensity Red LED | +5VDC | $\pm 200\text{mV}$ | 35.1 (1.38) 22.4 (0.88) | 811-1006-ND | 46.22 | 43.51 | 42.15 | DMS-20PC-3-RL-C |
| | | +5VDC | $\pm 2\text{V}$ | 35.1 (1.38) 22.4 (0.88) | 811-1007-ND | 46.22 | 43.51 | 42.15 | DMS-20PC-1-RH-C |
| | | +5VDC | $\pm 20\text{V}$ | 35.1 (1.38) 22.4 (0.88) | 811-1008-ND | 46.22 | 43.51 | 42.15 | DMS-20PC-0-GS-C |
| | Standard Green LED | +5VDC | $\pm 200\text{mV}$ | 35.1 (1.38) 22.4 (0.88) | 811-1009-ND | 42.19 | 39.72 | 38.48 | DMS-20PC-1-GS-C |
| | | +5VDC | $\pm 2\text{V}$ | 35.1 (1.38) 22.4 (0.88) | 811-1010-ND | 42.19 | 39.72 | 38.48 | DMS-20PC-2-GS-C |
| | | +5VDC | $\pm 20\text{V}$ | 35.1 (1.38) 22.4 (0.88) | 811-1011-ND | 50.24 | 47.28 | 45.81 | DMS-20PC-0-BS-C |
| Standard Blue LED | +5VDC | $\pm 200\text{mV}$ | 35.1 (1.38) 22.4 (0.88) | 811-1012-ND | 50.24 | 47.28 | 45.81 | DMS-20PC-1-BS-C | |
| | +5VDC | $\pm 2\text{V}$ | 35.1 (1.38) 22.4 (0.88) | 811-1013-ND | 50.24 | 47.28 | 45.81 | DMS-20PC-2-BS-C | |
| | +5VDC | $\pm 20\text{V}$ | 35.1 (1.38) 22.4 (0.88) | 811-1014-ND | 32.15 | 30.26 | 29.32 | DMS-20LCD-0-5-C | |
| DMS-20LCD | Standard LCD | +5VDC | $\pm 200\text{mV}$ | 35.1 (1.38) 22.4 (0.88) | 811-1015-ND | 32.15 | 30.26 | 29.32 | DMS-20LCD-1-5-C |
| | | +5VDC | $\pm 2\text{V}$ | 35.1 (1.38) 22.4 (0.88) | 811-1016-ND | 32.15 | 30.26 | 29.32 | DMS-20LCD-2-5-C |
| | | +5VDC | $\pm 20\text{V}$ | 35.1 (1.38) 22.4 (0.88) | 811-1017-ND | 30.14 | 28.37 | 27.49 | DMS-20LCD-0-9-C |
| | Backlit LCD | +5VDC | $\pm 200\text{mV}$ | 35.1 (1.38) 22.4 (0.88) | 811-1018-ND | 30.14 | 28.37 | 27.49 | DMS-20LCD-1-9-C |
| | | +5VDC | $\pm 2\text{V}$ | 35.1 (1.38) 22.4 (0.88) | 811-1019-ND | 34.15 | 32.15 | 31.14 | DMS-20LCD-1-5B-C |
| | | +5VDC | $\pm 20\text{V}$ | 55.1 (2.17) 23.4 (0.92) | 811-1020-ND | 54.25 | 51.06 | 49.47 | DMS-30PC-1-RS-C |
| DMS-30PC | Standard Red LED | +5VDC | $\pm 20\text{V}$ | 55.1 (2.17) 23.4 (0.92) | 811-1021-ND | 54.25 | 51.06 | 49.47 | DMS-30PC-2-RS-C |
| | | +5VDC | $\pm 200\text{mV}$ | 55.1 (2.17) 23.4 (0.92) | 811-1022-ND | 58.28 | 54.85 | 53.14 | DMS-30PC-0-RL-C |
| | | +5VDC | $\pm 2\text{V}$ | 55.1 (2.17) 23.4 (0.92) | 811-1023-ND | 58.28 | 54.85 | 53.14 | DMS-30PC-1-RL-C |
| | Low Power Red LED | +5VDC | $\pm 20\text{V}$ | 55.1 (2.17) 23.4 (0.92) | 811-1024-ND | 58.28 | 54.85 | 53.14 | DMS-30PC-2-RL-C |
| | | +5VDC | $\pm 200\text{mV}$ | 55.1 (2.17) 23.4 (0.92) | 811-1025-ND | 58.28 | 54.85 | 53.14 | DMS-30PC-3-RL-C |
| | | +5VDC | $\pm 2\text{V}$ | 55.1 (2.17) 23.4 (0.92) | 811-1026-ND | 58.28 | 54.85 | 53.14 | DMS-30PC-1-RH-C |

◆ RoHS Compliant † BCD Output ‡ With Blade Terminals § With Split-Core Flying Lead CT ▲ With Flying-Lead CT

(Continued)

More Product Available Online: www.digikey.com

Toll-Free: 1-800-344-4539 • Phone 218-681-6674 • Fax: 218-681-3380

NEW!



Digital Panel Meters (Cont.)

Formerly **DATEL**

| Series | Display | DPM Power | Input Range | Dimensions - mm (Inch) | | Digi-Key Part No. | Price Each | | | Murata Part No. |
|--|---|-----------------------|----------------------------|------------------------|--------------|-------------------|------------|--------|--------|-------------------------|
| | | | | A | B | | 1 | 10 | 50 | |
| DMS-30PC | Standard Green LED | +5VDC | ±200mV | 55.1 (2.17) | 23.4 (0.92) | 811-1027-ND | 54.25 | 51.06 | 49.47 | DMS-30PC-0-GS-C |
| | | +5VDC | ±2V | 55.1 (2.17) | 23.4 (0.92) | 811-1028-ND | 54.25 | 51.06 | 49.47 | DMS-30PC-1-GS-C |
| | Super Blue LED | +5VDC | ±200mV | 55.1 (2.17) | 23.4 (0.92) | 811-1029-ND | 54.25 | 51.06 | 49.47 | DMS-30PC-2-GS-C |
| | | +5VDC | ±2V | 55.1 (2.17) | 23.4 (0.92) | 811-1030-ND | 65.31 | 61.48 | 59.56 | DMS-30PC-3-GS-C |
| DMS-30DR | Super Bright Red LED, Sunlight Readable | +5VDC | ±200mV | 55.1 (2.17) | 23.4 (0.92) | 811-1031-ND | 65.31 | 61.48 | 59.56 | DMS-30PC-1-B5-C |
| | | +5VDC | ±2V | 55.1 (2.17) | 23.4 (0.92) | 811-1032-ND | 65.31 | 61.48 | 59.56 | DMS-30PC-2-B5-C |
| | | +5VDC | ±200mV | 55.1 (2.17) | 23.4 (0.92) | 811-1033-ND | 65.31 | 61.48 | 59.56 | DMS-30DR-0-R-C |
| | | +5VDC | ±2V | 55.1 (2.17) | 23.4 (0.92) | 811-1034-ND | 65.31 | 61.48 | 59.56 | DMS-30DR-1-R-C |
| DMS-30LCD | Standard LCD | +5VDC | ±200mV | 55.1 (2.17) | 23.4 (0.92) | 811-1035-ND | 65.31 | 61.48 | 59.56 | DMS-30DR-2-R-C |
| | | +5VDC | ±2V | 55.1 (2.17) | 23.4 (0.92) | 811-1036-ND | 48.23 | 45.40 | 43.98 | DMS-30LCD-0-5-C |
| | | +5VDC | ±20V | 55.1 (2.17) | 23.4 (0.92) | 811-1037-ND | 48.23 | 45.40 | 43.98 | DMS-30LCD-1-5-C |
| | | +9VDC | ±200mV | 55.1 (2.17) | 23.4 (0.92) | 811-1039-ND | 48.23 | 45.40 | 43.98 | DMS-30LCD-2-5-C |
| DM-31 | Standard Red LED | +5VDC | ±2V | 74.2 (2.92) | 33.5 (1.32) | 811-1042-ND | 105.91 | 99.68 | 96.57 | DM-3100M-1 |
| | | +5VDC | ±2V | 88.9 (3.50) | 50.8 (2.00) | 811-1043-ND | 94.01 | 88.48 | 85.72 | DM-31-1 |
| DM-LX3 | Standard LCD | +5VDC | ±2V | 95.1 (3.75) | 53.8 (2.12) | 811-1044-ND | 184.45 | 173.60 | 168.18 | DM-3100B-1 |
| | | | ±2V | 102.0 (4.00) | 50.8 (2.00) | 811-1045-ND | 111.86 | 105.28 | 101.99 | DM-LX3-1 |
| 4 1/2 Digit, Digital Panel Meters | | | | | | | | | | |
| DMS-40PC | Standard Red LED | +5VDC | ±2V | 55.1 (2.17) | 23.4 (0.92) | 811-1046-ND | 78.37 | 73.76 | 71.46 | DMS-40PC-1-RS-C |
| | | +5VDC | ±20V | 55.1 (2.17) | 23.4 (0.92) | 811-1047-ND | 78.37 | 73.76 | 71.46 | DMS-40PC-2-RS-C |
| | Low Power Red LED | +5VDC | ±2V | 55.1 (2.17) | 23.4 (0.92) | 811-1048-ND | 82.38 | 77.54 | 75.12 | DMS-40PC-1-RL-C |
| | | +5VDC | ±20V | 55.1 (2.17) | 23.4 (0.92) | 811-1049-ND | 82.38 | 77.54 | 75.12 | DMS-40PC-2-RL-C |
| | High-Intensity Red LED | +5VDC | ±2V | 55.1 (2.17) | 23.4 (0.92) | 811-1050-ND | 86.41 | 81.33 | 78.79 | DMS-40PC-1-RL-BCD-C |
| | | +5VDC | ±2V | 55.1 (2.17) | 23.4 (0.92) | 811-1051-ND | 82.38 | 77.54 | 75.12 | DMS-40PC-1-RL-C |
| DMS-40LCD | Standard LCD | +5VDC | ±200mV/±2V | 55.1 (2.17) | 23.4 (0.92) | 811-1052-ND | 78.37 | 73.76 | 71.46 | DMS-40PC-1-GS-C |
| | | +5VDC | ±2V/±20V | 55.1 (2.17) | 23.4 (0.92) | 811-1053-ND | 78.37 | 73.76 | 71.46 | DMS-40PC-2-GS-C |
| DM-4101 | Standard Red LED | +5VDC | ±2V | 74.2 (2.92) | 33.5 (1.32) | 811-1054-ND | 159.46 | 150.08 | 145.39 | DM-4101M-1 |
| | | +5VDC | ±2V | 95.1 (3.75) | 53.8 (2.12) | 811-1055-ND | 157.08 | 147.84 | 143.22 | DM-4101L-1 |
| 3 1/2 Digit, Control Monitors — RoHS Compliant | | | | | | | | | | |
| DMS-20PC | Low Power Red LED | +5 ~ 40VDC | 4.9 ~ 5.1V | 35.1 (1.38) | 22.4 (0.88) | 811-1083-ND | 78.37 | 73.76 | 71.46 | DMS-20PC-0-5-24RL-C |
| | Bright Blue LED | +5VDC | 4.9 ~ 5.1V | 35.1 (1.38) | 22.4 (0.88) | 811-1084-ND | 82.38 | 77.54 | 75.12 | DMS-20PC-0-5-58S-C |
| 3 - 3 1/2 Digit, Self-Powered Voltage Monitors — RoHS Compliant | | | | | | | | | | |
| DMS-20PC | Standard Red LED | — | +4.5 ~ +19.99VDC | 35.1 (1.38) | 22.4 (0.88) | 811-1060-ND | 50.24 | 47.28 | 45.81 | DMS-20PC-0-DCM-C |
| | | — | +8.0 ~ +50VDC | 35.1 (1.38) | 22.4 (0.88) | 811-1062-ND | 50.24 | 47.28 | 45.81 | DMS-20PC-1-DCM-C |
| | | — | +30 ~ +264VDC | 35.1 (1.38) | 22.4 (0.88) | 811-1064-ND | 50.24 | 47.28 | 45.81 | DMS-20PC-2-DCM-C |
| | | — | +2 ~ +11VDC | 35.1 (1.38) | 22.4 (0.88) | 811-1065-ND | 50.24 | 47.28 | 45.81 | DMS-20PC-3-DCM-C |
| | | — | -36 ~ -75VDC | 35.1 (1.38) | 22.4 (0.88) | 811-1066-ND | 50.24 | 47.28 | 45.81 | DMS-20PC-7-DCM-C |
| | | — | 85 ~ 264VAC | 35.1 (1.38) | 22.4 (0.88) | 811-1067-ND | 56.27 | 52.96 | 51.31 | DMS-20PC-1-LM-C |
| | Standard Blue LED | — | 85 ~ 264VAC | 35.1 (1.38) | 22.4 (0.88) | 811-1069-ND | 56.27 | 52.96 | 51.31 | DMS-20PC-1-LM-F-C |
| | | — | 240 ~ 310VAC | 35.1 (1.38) | 22.4 (0.88) | 811-1071-ND | 56.27 | 52.96 | 51.31 | DMS-20PC-2-LM-C |
| | | — | 350 ~ 600VAC | 35.1 (1.38) | 22.4 (0.88) | 811-1072-ND | 60.28 | 56.74 | 54.97 | DMS-20PC-3-LM-C |
| | | — | 85 ~ 140VAC | 35.1 (1.38) | 22.4 (0.88) | 811-1073-ND | 56.27 | 52.96 | 51.31 | DMS-20PC-1-FM-C |
| | | — | 170 ~ 264VAC | 35.1 (1.38) | 22.4 (0.88) | 811-1074-ND | 56.27 | 52.96 | 51.31 | DMS-20PC-3-FM-C |
| | | — | +4.5 ~ +19.99VDC | 35.1 (1.38) | 22.4 (0.88) | 811-1061-ND | 59.28 | 55.80 | 54.05 | DMS-20PC-0-DCM-B-C |
| DMS-20LCD | Standard LCD | — | +8.0 ~ +50VDC | 35.1 (1.38) | 22.4 (0.88) | 811-1063-ND | 59.28 | 55.80 | 54.05 | DMS-20PC-1-DCM-B-C |
| | | — | 85 ~ 264VAC | 35.1 (1.38) | 22.4 (0.88) | 811-1068-ND | 65.31 | 61.48 | 59.56 | DMS-20PC-1-LM-B-C |
| | | — | 85 ~ 264VAC | 35.1 (1.38) | 22.4 (0.88) | 811-1070-ND | 65.31 | 61.48 | 59.56 | DMS-20PC-1-LM-BF-C |
| | | — | +6.5 ~ +18VDC | 35.1 (1.38) | 22.4 (0.88) | 811-1058-ND | 30.14 | 28.37 | 27.49 | DMS-20LCD-0-DCM-C |
| | | +5VDC | +8.0 ~ +50VDC | 35.1 (1.38) | 22.4 (0.88) | 811-1059-ND | 30.14 | 28.37 | 27.49 | DMS-20LCD-1-DCM-C |
| 3 1/2 Digit, Loop-Powered Process Monitors — RoHS Compliant | | | | | | | | | | |
| DMS-20PC | Bright Red LED, Unipolar | — | +4 ~ +20mA | 35.1 (1.38) | 22.4 (0.88) | 811-1075-ND | 72.34 | 68.08 | 65.96 | DMS-20PC-4/20S-C |
| | Bright Red LED, Bipolar | — | +4 ~ +20mA | 35.1 (1.38) | 22.4 (0.88) | 811-1076-ND | 72.34 | 68.08 | 65.96 | DMS-20PC-4/20B-C |
| DMS-20LCD | Standard LCD, Unipolar | — | +3.8 ~ +20.4mA | 35.1 (1.38) | 22.4 (0.88) | 811-1077-ND | 54.25 | 51.06 | 49.47 | DMS-20LCD-4/20S-C |
| DMS-30PC | Standard Red, Full-Size LED | — | +3.5 ~ +22mA | 55.1 (2.17) | 23.4 (0.92) | 811-1080-ND | 84.39 | 79.43 | 76.95 | DMS-30PC-4/20S-24RS-1-C |
| | High-Intensity Blue, Full-Size LED | — | +3.5 ~ +22mA | 55.1 (2.17) | 23.4 (0.92) | 811-1081-ND | 94.44 | 88.88 | 86.11 | DMS-30PC-4/20S-24BS-1-C |
| DMS-30LCD | Standard LCD, Unipolar | — | +3.8 ~ +20.4mA | 55.1 (2.17) | 23.4 (0.92) | 811-1078-ND | 72.34 | 68.08 | 65.96 | DMS-30LCD-4/20S-C |
| 4 1/2 Digit, Loop-Powered Process Monitors — RoHS Compliant | | | | | | | | | | |
| DMS-40PC | Standard Red, Full-Size LED | — | +3.7 ~ +20.4mA | 55.1 (2.17) | 23.4 (0.92) | 811-1082-ND | 116.55 | 109.70 | 106.27 | DMS-40PC-4/20S-24RS-1-C |
| DMS-40LCD | Standard LCD | — | +3.8 ~ +20.4mA | 55.1 (2.17) | 23.4 (0.92) | 811-1079-ND | 110.52 | 104.02 | 100.77 | DMS-40LCD-4/20S-C |
| Ammeters — RoHS Compliant | | | | | | | | | | |
| ACA5-20PC | Standard Red LED | 85 ~ 264VAC @ 50/60Hz | 50.0A @ 45~450Hz | 35.1 (1.38) | 22.4 (0.88) | 811-1103-ND | 72.34 | 68.08 | 65.96 | ACA5-20PC-1-AC1-RL-C |
| | | 85 ~ 264VAC @ 50/60Hz | 100.0A @ 45~450Hz | 35.1 (1.38) | 22.4 (0.88) | 811-1104-ND | 72.34 | 68.08 | 65.96 | ACA5-20PC-3-AC1-RL-C |
| | | 85 ~ 264VAC @ 50/60Hz | 199.9A @ 45~450Hz | 35.1 (1.38) | 22.4 (0.88) | 811-1105-ND | 72.34 | 68.08 | 65.96 | ACA5-20PC-5-AC1-RL-C |
| | | 85 ~ 264VAC @ 50/60Hz | 500A @ 45~450Hz | 35.1 (1.38) | 22.4 (0.88) | 811-1106-ND | 72.34 | 68.08 | 65.96 | ACA5-20PC-9-AC1-RL-C |
| DCA5-20PC | Low Power Red LED | +5 ~ 40VDC | 5.00A/50.0A/500A | 35.1 (1.38) | 22.4 (0.88) | 811-1088-ND | 50.24 | 47.28 | 45.81 | DCA5-20PC-1-DC1-RL-C |
| | | +8 ~ 36VDC | 5.00A/50.0A/500A | 35.1 (1.38) | 22.4 (0.88) | 811-1089-ND | 59.28 | 55.80 | 54.05 | DCA5-20PC-1-DC4-RL-C |
| | | +8 ~ 36VDC | 1.00A/10.00A/100.0A/1000A | 35.1 (1.38) | 22.4 (0.88) | 811-1090-ND | 59.28 | 55.80 | 54.05 | DCA5-20PC-2-DC4-RL-C |
| | | +8 ~ 36VDC | 1.999A/19.99A/199.9A/1999A | 35.1 (1.38) | 22.4 (0.88) | 811-1091-ND | 59.28 | 55.80 | 54.05 | DCA5-20PC-6-DC4-RL-C |
| Ammeters With Built-In Shunts — RoHS Compliant | | | | | | | | | | |
| DCA-20PC | Low Power Red LED | +8 ~ 36VDC | 199.9mA | 35.1 (1.38) | 22.4 (0.88) | 811-1085-ND | 64.29 | 60.52 | 58.63 | DCA-20PC-4-DC4-RL-C |
| | | +8 ~ 36VDC | 1.999A | 35.1 (1.38) | 22.4 (0.88) | 811-1086-ND | 64.29 | 60.52 | 58.63 | DCA-20PC-5-DC4-RL-C |
| | | +5 ~ 40VDC | 1.999A | 35.1 (1.38) | 22.4 (0.88) | 811-1087-ND | 54.25 | 51.06 | 49.47 | DCA-20PC-5-DC1-RL-C |
| Ammeters With Built-In Current Transformers — RoHS Compliant | | | | | | | | | | |
| ACA-20PC | Standard Red LED | 85 ~ 264VAC @ 50/60Hz | 1.999A @ 45~450Hz | 35.1 (1.38) | 22.4 (0.88) | 811-1098-ND | 78.37 | 73.76 | 71.46 | ACA-20PC-1-AC1-RL-C |
| | | 85 ~ 264VAC @ 50/60Hz | 19.99A @ 45~450Hz | 35.1 (1.38) | 22.4 (0.88) | 811-1099-ND | 78.37 | 73.76 | 71.46 | ACA-20PC-2-AC1-RL-C |
| | | 85 ~ 264VAC @ 50/60Hz | 50.0A @ 45~450Hz | 35.1 (1.38) | 22.4 (0.88) | 811-1100-ND | 84.39 | 79.43 | 76.95 | ACA-20PC-3-AC1-RL-C |
| | | 85 ~ 264VAC @ 50/60Hz | 100.0A @ 45~450Hz | 35.1 (1.38) | 22.4 (0.88) | 811-1101-ND | 84.39 | 79.43 | 76.95 | ACA-20PC-4-AC1-RL-C |
| ACA-20RM | Low Power Red LED | 85 ~ 264VAC @ 50/60Hz | 30.0A @ 45~450Hz | 35.1 (1.38) | 22.4 (0.88) | 811-1102-ND | 78.37 | 73.76 | 71.46 | DMS-30798-C |
| | | 85 ~ 140VAC @ 50/60Hz | 1.999A | 53.34 (2.10) | 44.45 (1.75) | 811-1111-ND | 94.44 | 88.88 | 86.11 | ACA-20RM-1-AC3-RL-C |
| | | 85 ~ 140VAC @ 50/60Hz | 19.99A | 53.34 (2.10) | 44.45 (1.75) | 811-1112-ND | 94.44 | 88.88 | 86.11 | ACA-20RM-2-AC3-RL-C |
| | | 85 ~ 140VAC @ 50/60Hz | 50.0A | 53.34 (2.10) | 35.56 (1.40) | 811-1113-ND | 98.46 | 92.68 | 89.78 | ACA-20RM-4-AC3-RL-C |
| | | 85 ~ 140VAC @ 50/60Hz | 30.0A | 53.34 (2.10) | 35.56 (1.40) | 811-1114-ND | 94.44 | 88.88 | 86.11 | ACA-20RM-5-AC3-RL-C |

◆ RoHS Compliant † BCD Output ‡ With Blade Terminals § With Split-Core Flying Lead CT ▲ With Flying-Lead CT

Accessories

| Description | Digi-Key Part No. | Price Each | Murata Part No. |
|---|-------------------|------------|-----------------|
| 50mV Base Mount DC Shunts — RoHS Compliant | | | |
| 5A Rated Current | 811-1092-ND | 23.80 | 3020-01097-0 |
| 20A Rated Current | 811-1093-ND | 23.80 | 3020-01098-0 |
| 50A Rated Current | 811-1094-ND | 23.80 | 3020-01099-0 |
| 100A Rated Current | 811-1095-ND | 23.80 | 3020-01099-0 |
| 200A Rated Current | 811-1096-ND | 29.75 | 3020-01101-0 |
| 500A Rated Current | 811-1097-ND | 29.75 | 3020-01103-0 |
| AC Current Transformers | | | |
| 50:5A Current Ratio | 811-1107-ND | 29.75 | 7020-01036-0 |
| 100:5A Current Ratio | 811-1108-ND | 29.75 | 7020-01038-0 |
| 200:5A Current Ratio | 811-1109-ND | 29.75 | 7020-01040-0 |
| 500:5A Current Ratio | 811-1110-ND | 29.75 | 39-3681409 |

| Description | Digi-Key Part No. | Price Each | Murata Part No. |
|--|-------------------|------------|----------------------|
| Switching Regulators — RoHS Compliant | | | |
| 3.3VDC/0.5A Output | 811-1115-ND | 11.78 | 7803SR-C |
| 5.0VDC/0.5A Output | 811-1116-ND | 11.78 | 7805SR-C |
| 12.0VDC/0.4A Output | 811-1117-ND | 11.78 | 7812SR-C |
| 3.3VDC/2.0A Output | 811-1118-ND | 14.01 | 78SR-3.3/2-C |
| 5.0VDC/2.0A Output | 811-1119-ND | 14.01 | 78SR-5/2-C |
| Power Supplies - Chassis Mount — RoHS Compliant | | | |
| 5W, 5VDC/1A Out | 811-1120-ND | 64.26 | 60.48 [DMS-PS1-CM-C] |
| Panel Cutout Punch | | | |
| For DMS-20-CP Series | 811-1121-ND | 382.50 | 360.00 [DMS-20-CP] |
| | | | |