



# CY7B923 HOTLink



The **CY7B923 HOTLink Transmitter** and **CY7B933 HOTLink Receiver** are point-to-point communications building blocks that transfer data over high-speed serial links (fiber, coax, and twisted pair). Standard HOTLink data rates range from 160-330 Mbts/second. Higher speed HOTLink is also available for high-speed applications (160-400 Mbts/second), as well as for those low-cost applications HOTLink-155 (150-160 Mbts/second operations).

### Features:

- Fibre-Channel compliant • IBM ESCON compliant • DVB-ASI compliant • ATM compliant • B/10B coded or 10-bit unencoded • Standard HOTLink: 160–330Mbps • High-speed HOTLink 160–400 Mbps for high-speed applications • Low-speed HOTLink: 150–160Mbps for low-cost fiber

### Applications:

- TTL synchronous I/O • No external phase-locked-loop (PLL) components • Triple PECL 100K serial outputs
- Dual PECL 100K serial inputs • Low power: 350mW (Tx), 650mW (Rx) • Compatible with fiber optic modules, coaxial cable, and twisted pair media • Built-In Self-Test • Single +5V supply • 28-pin SOIC/PLCC/LCC • 0.8 BiCMOS

Description	Package	Digi-Key Part No.	Price Each			Cypress Part No.
			1	25	100	
Transmitter, Standard Speed	28-PLCC	428-1706-5-ND	40.80	32.65	27.55	CY7B923-JXC
	28-SOIC	428-1707-5-ND	40.80	32.65	27.55	CY7B923-SXC
Receiver, Standard Speed	28-PLCC	428-1708-5-ND	40.80	32.65	27.55	CY7B933-JXC
	28-SOIC	428-1709-5-ND	40.80	32.65	27.55	CY7B933-SXC

## C Developer Kits

### CY3674

The development kits for the EZ-USB FX™ family provide complete hardware and software solutions for accelerating the firmware and device driver development for all the products in the family. The development kits use the actual silicon for the entire development. Software utilities and example of firmware allow the user to generate USB traffic in hours, not weeks! Includes an evaluation version of the 8051 Keil Software Tools in the Full Speed USB 2.0 development kit. The evaluation version of the C-Compiler lets the designer write 8051 microcontroller applications in C and still get the efficiency and speed of assembly language. Advanced features from Keil Tools include the ability to single step through code. This makes it easy to detect errors, handle source level debugging, and set breakpoints. With the ability to debug code one line at a time and to quickly compile and one-step download new code, developers have a more efficient means to complete firmware faster than using emulators. The supplied Keil Tools are fully functional, but are limited in object size to 4 kilobytes.

**Devices Supported:** CY7C64713-56LFXC, CY7C64713-100AXC, CY7C64713-128AXC

### Kit Includes:

- EZ-USB Development Board with CY7C64713-128AXC • Peripheral Board for prototyping • USB cable
- RS-232 9-pin to 9-pin cable

**428-1681-ND** EZ-USB FX1 Development Kit ..... **355.74**

### CY3684

The CY3684 development kit for the EZ-USB FX2LP™ family provides complete hardware and software solutions for accelerating the firmware and device driver development for all of the products in the family. The development kits use the actual silicon for the entire development. Software utilities and example firmware allow the user to generate USB traffic in hours, not weeks! Includes an evaluation version of the 8051 Keil Software Tools. The evaluation version of the C-Compiler lets the designer write 8051 microcontroller applications in C and still get the efficiency and speed of assembly language. The supplied Keil tools are fully functional, but are limited in object size to 4 kilobytes.

### Kit includes:

- EZ-USB development board • Peripheral board for prototyping • USB cable • RS232 9-pin to 9-pin cable

**428-1677-ND** Development Kit for EZ-USB FX2LP ..... **381.15**

### SL11R-DK

The SL11R from Cypress, is a low cost, full speed Universal Serial Bus (USB) RISC based Controller. The SL11R contains a 16-bit RISC processor with built-in BIOS ROM that greatly reduces firmware development time. This unique architecture provides the ability to upgrade products, in the field, without changing the peripheral hardware. The processor can execute code either from internal ROM/DRAM or external DRAM, SRAM and ROM. Email support.

- HW reference design for SL11R evaluation board • Assembler/Debugger and built in emulator
- Application notes • BIOS ROM information • System Software demo program source code • Generic WDM mini-port driver for WIN98/2000-object code • 2 sample chips

**428-1344-ND** SL11 Development Tools ..... **359.37**

### CY4636

WirelessUSB LP RDK (CY4636) provides an exemplary implementation of a 2:1, bidirectional Wireless desktop keyboard and mouse to single wireless receiver. The RDK will help jump-start your Keyboard and Mouse development using WirelessUSB LP (CYRF6936) Radio System on Chip. WirelessUSB LP is the next generation WirelessUSB device, with high data throughput and low power designed to operate in 2.4 GHz ISM band. WirelessUSB has many powerful features that allow users to create never before seen radio applications.

- CYRF6936 WirelessUSB LS transceiver • Optical Sensor Mouse • WirelessUSB keyboard
- Batteries • CD

**428-1858-ND** Wireless USB REF Kit ..... **180.59**

### CY3655

The enCoRe™ II development system, based on the highly refined PSoC™ (Programmable System-on-Chip™) tools, supplies the user with an in-circuit emulator (ICE) that works in conjunction with actual silicon to provide an accurate and efficient development system. The PSoC Designer™ software consists of a graphical user interface, assembler, C-Compiler, linker and debugger for a highly integrated code development environment. A compliant USB "User Module" along with PS/2 and other peripheral User Modules simplifies the learning curve and speeds development time.

- Application Board enCoRe II Pod • Wireless enCoRe II Pod • PDIP feet • Modular Programmer Base Board • Programming Adapter Plug • USB Cable PS/2 Male to Male Cable • Software • Printed Documentation

**428-1773-ND** Development Kit for enCoRe II ..... **846.52**

**428-1774-ND** Extension Kit for enCoRe II ..... **446.49**

## TOSHIBA 8, 16, and 32-Bit Flash Microcontrollers

Leading Innovation >>>

Toshiba 8-bit microcontrollers feature low-power consumption and low voltage operation. The on-chip peripherals options include LCD, VFT and LED display drivers. The 870/C series has a single register bank to increase C-Compiler efficiency.

- Minimum Instruction cycle time: 0.25µs at 16MHz • Low-power modes including HALT, IDLE and clock gear and dual clocks • Powerful instruction set with 731 instructions including multiply, divide, 16-bit operations, bit manipulations, etc. • On-chip peripherals including A/D, PWM, UARTS and LCD • Operating Temperature: -40° ~ 85°C

**Kits Include:** Evaluation Board, C-Compiler (3000 lines per module), Assembler, Linker, RS-232 Cable, Batteries, Quick Start Guide, Datasheet, Manuals, CD with Tools

Memory Size		I/O	Supply Voltage	Package	Digi-Key Part No.	Price Each			Toshiba Part No.
EPROM	RAM					1	25	100	
512K	24KB	143	2.7 - 3.6	193-FBGA	TMP19A43FDXBG-ND◆	9.17	8.26	7.32	TMP19A43FDXBG
2MB	64KB	209	2.7 - 3.6	281-FBGA	TMP19A64F20AXBG-ND◆	30.24	27.23	24.14	TMP19A64F20AXBG
32K	2K	39	1.8 - 3.6	64-QFP	TMP86FM29FG-ND◆	4.07	3.26	2.53	TMP86FM29FG
32K	2K	39	1.8 - 3.6	64-LQFP	TMP86FM29UG-ND◆	4.07	3.26	2.53	TMP86FM29UG
32K	2K	56	1.8 - 3.6	64-QFP	TMP86FM48FG-ND◆	5.81	4.65	3.93	TMP86FM48FG
32K	2K	56	1.8 - 3.6	64-LQFP	TMP86FM48UG-ND◆	5.74	4.59	3.88	TMP86FM48UG
48K	2K	48	1.8 - 3.6	80-LQFP	TMP86FP24FG-ND◆	—	—	3.08	TMP86FP24FG
8K	256	22	2.7 - 5.5	30-SSOP	TMP86F807MGJY-ND◆	3.92	3.14	2.44	TMP86F807MG(EY)
8K	256	24	2.7 - 5.5	30-SSOP	TMP86F808DMGJY-ND◆	3.92	3.14	2.44	TMP86F808DMG(EY)
16K	512	26	4.5 - 5.5	32-SDIP	TMP86FH09NGZM-ND◆	1.84	1.48	1.15	TMP86FH09NG(ZM)
16K	512	24	2.7 - 5.5	30-SSOP	TMP86FH12MGZ-ND◆	2.61	2.10	1.63	TMP86FH12MG(Z)
16K	512	33	2.7 - 5.5	42-SDIP	TMP86FH46ANGZ-ND◆	3.63	2.91	2.46	TMP86FH46ANG(Z)
16K	512	35	2.7 - 5.5	44-LQFP	TMP86FH47UG-ND◆	2.09	1.68	1.41	TMP86FH47UG
60K	2K	48	2.7 - 5.5	64-LQFP	TMP86FS23UGJZ-ND◆	3.47	2.78	2.16	TMP86FS23UG(JZ)
60K	1K	55	2.7 - 5.5	80-LQFP	TMP86FS27FG-ND◆	6.88	5.51	4.65	TMP86FS27FG
60K	2K	62	2.7 - 5.5	80-LQFP	TMP86FS28DFGJZ-ND◆	3.67	2.94	2.48	TMP86FS28DFG(JZ)
60K	2K	62	2.7 - 5.5	80-QFP	TMP86FS28FGTZ-ND◆	3.67	2.94	2.48	TMP86FS28FG(TZ)
60K	2KB	56	2.7 - 5.5	60-QFP	TMP86FS49AFGZ-ND◆	3.78	3.02	2.55	TMP86FS49AFG(Z)
60K	2KB	56	2.7 - 5.5	60-LQFP	TMP86FS49AUGJZ-ND◆	3.78	3.02	2.55	TMP86FS49AUG(JZ)
60K	2KB	91	2.7 - 5.5	100-QFP	TMP86FS64FGTZ-ND◆	4.02	3.22	2.51	TMP86FS64FG(TZ)
16K	512	32	1.8 - 5.5	44-LQFP	TMP86PH22UGJZ-ND◆	3.19	2.55	1.99	TMP86PH22UG(JZ)
128K	4KB	61	2.4 - 3.6	100-LQFP	TMP91FW40FGJZ-ND◆	5.42	4.34	3.66	TMP91FW40FG(JZ)
256K	16KB	81	2.4 - 3.6	100-LQFP	TMP91FY42FGJZ-ND◆	7.41	6.68	5.92	TMP91FY42FG(JZ)
128K	8KB	81	2.4 - 3.6	100-QFP	TMP91FW60DFGTZ-ND◆	5.42	4.34	3.66	TMP91FW60DFG(TZ)
128K	8KB	83	2.4 - 3.6	100-LQFP	TMP91FW60FGBJZ-ND◆	5.42	4.34	3.66	TMP91FW60FBG(JZ)
8K	288KB	136	2.4 - 3.6	228-FBGA	TMP92C226AXBG-ND◆	7.26	6.54	5.80	TMP92C226AXBG
86FH47 Starter Kit .....					BMSKTOPASF47AND-ND	71.84	—	—	BMSKTOPASF47(AND)
86FM29 Starter Kit .....					BMSKTOPASFMA-ND	71.84	—	—	BMSKTOPASFMA(AND)
86FM29 Starter Kit .....					BMSKTOPASFMA48AND-ND	71.84	—	—	BMSKTOPASFMA48(AND)
TMP86FS49 Evaluation Kit .....					BMSKTOPASF64S49A-ND◆	71.84	—	—	BMSKTOPASF64S49(A)

◆ RoHS Compliant

**Free shipping on orders over £50! All prices are in British pound sterling and include duties.**

652 (UK091)

uk.digikey.com — FREEPHONE: 0-800-587-0991 • 0-800-904-7786 — FREEFAX: 0-800-587-0992 • 0-800-904-7783